


FIG. 277

ADJUSTABLE TWO ROD ROLLER HANGER



- Material:** Carbon steel axle with cast iron roller and socket ends.
- Finish:** Plain, electro-galvanized or painted.
- Service:** Designed for the suspension of pipe where longitudinal movement may occur due to expansion and contraction, and vertical adjustment is necessary.
- Approvals:** Complies with Federal Specification WW-H-171-E (Type# 42), A-A-1192 A (Type# 41) and Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 41).
- Ordering:** Specify roller size, figure number and finish. Please remember to consider insulation thickness when sizing rollers.
- Notes:** Available domestic

PIPE ROLLER SIZE	PIPE OD	AXLE SIZE	A	B	C	E	L	R	WGT EACH (lbs)	MAX REC LOAD (lbs)
2	2.375	$\frac{3}{8}$	$\frac{3}{8}$	$1\frac{1}{16}$	$4\frac{3}{8}$	$2\frac{3}{16}$	$5\frac{5}{8}$	$2\frac{7}{8}$	0.760	600
2½	2.875	$\frac{1}{2}$	$\frac{1}{2}$	$1\frac{1}{8}$	$5\frac{1}{8}$	$2\frac{5}{8}$	$6\frac{1}{2}$	$3\frac{1}{8}$	1.185	660
3	3.500	$\frac{1}{2}$	$\frac{1}{2}$	$2\frac{1}{8}$	$5\frac{5}{8}$	$2\frac{7}{8}$	7	$3\frac{3}{4}$	1.385	700
3½	4.000	$\frac{1}{2}$	$\frac{1}{2}$	$2\frac{1}{2}$	$5\frac{7}{8}$	$3\frac{1}{4}$	$7\frac{1}{4}$	$3\frac{7}{8}$	1.500	750
4	4.500	$\frac{1}{2}$	$\frac{5}{8}$	$2\frac{13}{16}$	7	$3\frac{13}{16}$	$8\frac{9}{16}$	$4\frac{3}{4}$	2.110	750
5	5.563	$\frac{5}{8}$	$\frac{5}{8}$	$3\frac{3}{8}$	$8\frac{1}{8}$	$4\frac{3}{8}$	$9\frac{3}{4}$	$5\frac{3}{4}$	2.570	750
6	6.625	$\frac{3}{4}$	$\frac{3}{4}$	$3\frac{15}{16}$	$9\frac{3}{4}$	$4\frac{15}{16}$	$11\frac{5}{8}$	$6\frac{7}{8}$	4.395	1070
7	7.625	$\frac{3}{4}$	$\frac{3}{4}$	$4\frac{1}{2}$	$10\frac{1}{2}$	$5\frac{1}{4}$	$12\frac{1}{2}$	8	5.160	1100
8	8.625	$\frac{7}{8}$	$\frac{7}{8}$	$5\frac{1}{8}$	$12\frac{1}{8}$	$6\frac{3}{8}$	$14\frac{1}{4}$	$8\frac{7}{8}$	7.425	1350
10	10.750	$\frac{7}{8}$	$\frac{7}{8}$	$6\frac{1}{4}$	14	$7\frac{1}{2}$	$16\frac{1}{4}$	11	9.170	1730
12	12.750	$\frac{7}{8}$	$\frac{7}{8}$	$7\frac{5}{16}$	$15\frac{5}{8}$	$8\frac{9}{16}$	18	13	13.150	2400
14	14.000	$1\frac{1}{8}$	1	$8\frac{3}{8}$	$17\frac{3}{4}$	$9\frac{13}{16}$	$20\frac{1}{2}$	$14\frac{1}{4}$	18.745	3130
16	16.000	$1\frac{1}{4}$	1	$9\frac{1}{2}$	$20\frac{9}{16}$	$10\frac{15}{16}$	$23\frac{3}{8}$	$16\frac{5}{8}$	24.540	3970
18	18.000	$1\frac{1}{4}$	1	$10\frac{7}{16}$	22	$11\frac{1}{8}$	$24\frac{1}{8}$	$18\frac{9}{16}$	27.200	4200
20	20.000	$1\frac{1}{4}$	$1\frac{1}{4}$	$11\frac{1}{2}$	24	$13\frac{3}{8}$	27	$20\frac{1}{4}$	32.000	4550
24	24.000	$1\frac{1}{2}$	$1\frac{1}{2}$	$13\frac{1}{16}$	$28\frac{3}{4}$	$16\frac{5}{8}$	32	$24\frac{1}{4}$	54.000	6160
30	30.000	$1\frac{3}{4}$	$1\frac{1}{2}$	$17\frac{1}{4}$	$35\frac{5}{8}$	$19\frac{5}{8}$	$39\frac{3}{4}$	$30\frac{1}{4}$	82.000	7290

* Note: To be supplied with an additional roller on top. Making this a two rod, two roller hanger assembly.