

NTS

3/8"

2 SLOTS
3/4" x 1 1/2"

3/4"

3/8"

1" - 5 5/8"

1" - 3 3/4"

BOTTOM OF COVER

USE SOLID COVER AND CONCEALED LIFTING HOLE WHEN TOP IS BURIED BELOW GRADE

1 1/4"

3/8"

3/4"

3/4"

1 1/2"

3/4"

3/4"

1" - 3 3/4"

1" - 8 1/8"

1/4"

TOP OF COVER

SECTION A-A

NOTE: THE LETTERS "SEWER" SHALL BE CAST IN THE DEPRESSION IN TOP OF COVER 1" HIGH AND RAISED 3/8" HIGH AS SHOWN

MANHOLE FRAME AND COVER SHALL BE SIMILAR TO THAT STANDARD 106.02. VOOOT APPROVED DUCTILE IRON FRAME AND COVER MAY BE SUBSTITUTED

APPROXIMATE WEIGHT CAST IRON
FRAME: 2392 LBS.
COVER: 1372 LBS.

PLAN

1"

1" - 10"

1" - 8 1/4"

7/8"

3/4"

3/4"

5"


5"

2" - 0"

3/4"

SECTION B-B

**SEWER PROJECT
STANDARD MANHOLE
FRAME & COVER**



- NOTE: THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING A COPY OF THE LATEST EDITION OF THE FRANKLIN COUNTY "STANDARD SPECIFICATIONS FOR WATER AND SEWER SYSTEMS" (CHAPTER 22). A COPY OF THE SPECIFICATIONS MUST BE KEPT ON SITE AT ALL TIMES DURING CONSTRUCTION.

CONSTRUCTION OF ALL UTILITY LINES
AND APPURTENANCES SHALL BE AS PER
THE LATEST EDITION OF CHAPTER 22.