

STORM SEWER WORKSHEET

Structure Number		Pipe Length	Drainage Area	CI	Q25	Pipe Q	Pipe Size	Const. Grade	V	Vh	Q x Vh	Hyd. Grade	Frict. Loss	Flow Line Elevation	Top of Structure Elevation		Free Board	Hydraulic Elevation	Junction Loss	Angle	Bend Loss	Capacity	Q/Cap.	Discharge Velocity	
Upper	Lower	ft.	ac	c.f.s.	c.f.s.	c.f.s.	in.	%	f.p.s.	ft.	c.f.s.	n	ft.	Upper	Lower	ft.	Upper	Lower	ft.	(°)	ft.	c.f.s.		f.p.s.	
8	6	30	0.18	3.87	0.70	0.70	15	2.00%	0.57	0.01	0.00	0.01%	0.00	1120.52	1119.92	1123.30	1122.75	1.53	1121.25	1121.25	0.18		9.90	0.07	4.56
5	4	4	0.06	4.89	0.29	0.99	8	11.17%	2.84	0.12	0.12	0.57%	0.02	1119.50	1118.87	1123.00	1124.00	2.83	1119.56	1119.54		90	0.09	4.38	10.03
roof drain	3	202	0.04	7.11	0.28	1.27	8	2.30%	3.64	0.21	0.26	0.94%	1.90	1123.00	1118.32	1126.00	1118.32	2.33	1120.89	1118.99		90	0.14	1.99	6.01
6	2	228.52	0.35	6.16	2.35	3.62	15	1.00%	2.95	0.14	0.49	0.27%	0.81	1119.82	1117.54	1122.75	1121.98	1.50	1119.82	1119.01	0.32			7.00	5.71
2	1	152	0.33	6.16	2.03	5.65	15	9.50%	4.80	0.33	1.86	0.85%	0.99	1117.44	1116.00	1121.98	1120.00	2.97	1118.24	1117.25		45	0.15	21.57	14.77

HYDROLOGY WORKSHEET

C _{pervious} =	0.90
C _{impervious} =	0.33
I ₂ =	5.20
I ₁₀ =	6.80
I ₂₅ =	7.90
[Based on T _c = 5 min. Roanoke County]	

Structure	Impervious	Permeable	Atotal	Cweighted	Q2	Q10	Q25
2	0.26	0.07	0.33	0.78	1.34	1.75	2.03
5	0.03	0.03	0.06	0.62	0.19	0.25	0.29
6	0.32	0.03	0.35	0.85	1.55	2.03	2.35
8	0.05	0.13	0.18	0.49	0.46	0.60	0.69


Pipe #	Impervious	Permeable	Atotal	Cweighted	Q2	Q10	Q25
Roof Drain	0.04	0.00	0.04	0.90	0.19	0.24	0.28

INLET CALCULATIONS

Project Description Worksheet	Inlet #2	Project Description Worksheet	Inlet #5	Project Description Worksheet	Inlet #6	Project Description Worksheet	Inlet #8
Type	Grate Inlet	Type	Grate Inlet	Type	Grate Inlet	Type	Grate Inlet
Solve For	In Sag Spread	Solve For	In Sag Spread	Solve For	In Sag Spread	Solve For	In Sag Spread
Input Data							
Discharge	2.03 cfs	Discharge	0.29 cfs	Discharge	2.36 cfs	Discharge	0.46 cfs
Gutter Width	2 ft	Gutter Width	4 ft	Gutter Width	4.17 ft	Gutter Width	2 ft
Gutter Cross Slope	0.083 ft/ft	Gutter Cross Slope	0.14 ft/ft	Gutter Cross Slope	0.02 ft/ft	Gutter Cross Slope	0.02 ft/ft
Road Cross Slope	0.029 ft/ft	Road Cross Slope	0.14 ft/ft	Road Cross Slope	0.02 ft/ft	Road Cross Slope	0.02 ft/ft
Grate Width	2 ft	Grate Width	2 ft	Grate Width	2.5 ft	Grate Width	2 ft
Grate Length	2.5 ft	Grate Length	2 ft	Grate Length	2.5 ft	Grate Length	2 ft
Local Depression	2 in	Local Depression	12 in	Local Depression	3 in	Local Depression	2 in
Local Depression Width	2 ft	Local Depression Width	7 ft	Local Depression Width	2.5 ft	Local Depression Width	2 ft
Grate Type	P-50 mm (P-1-7/8")	Grate Type	P-50 mm (P-1-7/8")	Grate Type	P-50 mm (P-1-7/8")	Grate Type	P-50 mm (P-1-7/8")
Clogging	0 %	Clogging	0 %	Clogging	0 %	Clogging	10 %
Results							
Spread	5.88 ft	Spread	3.54 ft	Spread	8.29 ft	Spread	2.82 ft
Depth	0.28 ft	Depth	0 ft	Depth	0.17 ft	Depth	0.06 ft
Gutter Depression	1.3 in	Gutter Depression	0 in	Gutter Depression	0 in	Gutter Depression	0 in
Total Depression	3.3 in	Total Depression	12 in	Total Depression	3 in	Total Depression	2 in
Open Grate Area	4.5 ft²	Open Grate Area	3.6 ft²	Open Grate Area	5.6 ft²	Open Grate Area	3.2 ft²
Active Grate Weir Length	6.5 ft	Active Grate Weir Length	6 ft	Active Grate Weir Length	7.5 ft	Active Grate Weir Length	5.6 ft

PIPE CALCULATIONS


Project Description Worksheet	Pipe #7	Project Description Worksheet	Pipe #4	Project Description Worksheet	Pipe roof drain	Project Description Worksheet	Pipe #3	Project Description Worksheet	Pipe #1
Flow Element Method	Circular Channel Manning's Formula	Flow Element Method	Circular Channel Manning's Formula	Flow Element Method	Circular Channel Manning's Formula	Flow Element Method	Circular Channel Manning's Formula	Flow Element Method	Circular Channel Manning's Formula
Solve For	Channel Depth	Solve For	Channel Depth	Solve For	Channel Depth	Solve For	Channel Depth	Solve For	Channel Depth
Input Data									
Manning's Coefficient	0.013	Manning's Coefficient	0.012	Manning's Coefficient	0.012	Manning's Coefficient	0.012	Manning's Coefficient	0.012
Channel Slope	0.02 ft/ft	Channel Slope	0.155 ft/ft	Channel Slope	0.023 ft/ft	Channel Slope	0.01 ft/ft	Channel Slope	0.0095 ft/ft
Diameter	15 in	Diameter	8 in	Diameter	8 in	Diameter	15 in	Diameter	15 in
Discharge	0.7 cfs	Discharge	0.29 cfs	Discharge	0.28 cfs	Discharge	3.62 cfs	Discharge	5.65 cfs
Results									
Depth	0.23 ft	Depth	0.11 ft	Depth	0.17 ft	Depth	0.84 ft	Depth	0.87 ft
Flow Area	0.2 ft²	Flow Area	0 ft²	Flow Area	0.1 ft²	Flow Area	0.8 ft²	Flow Area	0.9 ft²
Wetted Perimeter	1.12 ft	Wetted Perimeter	0.55 ft	Wetted Perimeter	0.7 ft	Wetted Perimeter	1.99 ft	Wetted Perimeter	2.46 ft
Top Width	0 ft	Top Width	0 ft	Top Width	0 ft	Top Width	0 ft	Top Width	0 ft
Critical Depth	0.33 ft	Critical Depth	0.25 ft	Critical Depth	0.24 ft	Critical Depth	0.77 ft	Critical Depth	0.96 ft
Percent Full	16.7 %	Percent Full	16.1 %	Percent Full	25.4 %	Percent Full	51 %	Percent Full	69.4 %
Critical Slope	0.005233 ft/ft	Critical Slope	0.005554 ft/ft	Critical Slope	0.005539 ft/ft	Critical Slope	0.005511 ft/ft	Critical Slope	0.007362 ft/ft
Velocity	4.4 ft/s	Velocity	7.97 ft/s	Velocity	4.02 ft/s	Velocity	5.75 ft/s	Velocity	6.21 ft/s
Head	0.3 ft	Head	0.99 ft	Head	0.25 ft	Head	0.51 ft	Head	0.8 ft
Specific Energy	0.54 ft	Specific Energy	1.09 ft	Specific Energy	0.42 ft	Specific Energy	1.15 ft	Specific Energy	1.47 ft
Froude Number	1.92	Froude Number	5.16	Froude Number	2.04	Froude Number	1.43	Froude Number	1.23
Maximum Discharge	9.83 cfs	Maximum Discharge	5.54 cfs	Maximum Discharge	2.14 cfs	Maximum Discharge	7.53 cfs	Maximum Discharge	7.34 cfs
Discharge	9.14 cfs	Discharge	5.15 cfs	Discharge	1.99 cfs	Discharge	7 cfs	Discharge	6.82 cfs
Full Slope Full	0.000117 ft/ft	Full Slope Full	0.000491 ft/ft	Full Slope Full	0.000458 ft/ft	Full Slope Full	0.002676 ft/ft	Full Slope Full	0.006519 ft/ft
Flow Type	Supercritical	Flow Type	Supercritical	Flow Type	Supercritical	Flow Type	Supercritical	Flow Type	Supercritical



AVACSO-30-40 Minimum Standards


An erosion and sediment control program adopted by a district or locality must be consistent with the following criteria, techniques and methods:

- Permanent or temporary soil stabilization shall be applied to denuded areas within seven days after final grade is reached on any portion of the site. Temporary soil stabilization shall be applied within seven days to denuded areas that may not be at final grade but will remain dormant for longer than 30 days. Permanent stabilization shall be applied to areas that are to be left dormant for more than one year. SHOWN ON PLANS.
- During construction of the project, soil stockpiles and borrow areas shall be stabilized or protected with sediment trapping measures. The applicant is responsible for the temporary protection and permanent stabilization of all soil stockpiles on site as well as borrow areas and soil intentionally transported from the project site. SHOWN ON PLANS.
- A permanent vegetative cover shall be established on denuded areas not otherwise permanently stabilized. Permanent vegetation shall not be considered established until a ground cover is achieved that, is uniform, mature enough to survive and will inhibit erosion. SHOWN ON PLANS.
- Sediment basins and traps, perimeter dikes, sediment barriers and other measures intended to trap sediment shall be constructed as a first step in any land-disturbing activity and shall be made functional before upstate land disturbance takes place. SILT FENCE SHOWN ON PLANS.
- Stabilization measures shall be applied to earthen structures such as dams, dikes and diversions immediately after installation. NOT APPLICABLE.
- Sediment traps and sediment basins shall be designed and constructed based upon the total drainage area to be served by the trap or basin. NOT APPLICABLE NEITHER REQUIRED ON THIS PROJECT.
 - The minimum storage capacity of a sediment trap shall be 134 cubic yards per acre of drainage area and the trap shall only control drainage areas less than three acres.
 - Surface runoff from disturbed areas that is comprised of flow from drainage areas greater than or equal to three acres shall be controlled by a sediment basin. The minimum storage capacity of a sediment basin shall be 134 cubic yards per acre of drainage area. The outfall system shall, at a minimum, maintain the structural integrity of the basin during a twenty-five year storm of 24-hour duration. Runoff coefficients used in runoff calculations shall correspond to a bare earth condition or those conditions expected to exist while the sediment basin is utilized.
- Cut and fill slopes shall be designed and constructed in a manner that will minimize erosion. Slopes that are found to be eroding excessively within one year of permanent stabilization shall be provided with additional slope stabilizing measures until the problem is corrected. MAXIMUM SLOPE FOR THIS PROJECT IS 3 TO 1.
- Concentrated runoff shall not flow down cut or fill slopes unless contained within an adequate temporary or permanent channel, berm or slope drain structure. ALL RUNOFF IS PIPED.
- Whenever water seeps from a slope face, adequate drainage or other protection shall be provided. IF ENCOUNTERED DURING CONSTRUCTION THEN APPROPRIATE MEASURE WILL BE PROVIDED.
- All storm sewer inlets that are made operable during construction shall be protected so that sediment-laden water cannot enter the conveyance system without first being filtered or otherwise treated to remove sediment. SHOWN ON PLANS.
- Before newly constructed stormwater conveyance channels or pipes are made operational, adequate outlet protection and any required temporary or permanent channel lining shall be installed in both the conveyance channel and receiving channel. NOT APPLICABLE.
- When work in a live watercourse is performed, precautions shall be taken to minimize encroachment, control sediment transport and stabilize the work area to the greatest extent possible during construction. Nonerodible material shall be used for the construction of easements and collardans. Earthen fill may be used for these structures if removed by nonerodible cover material. NOT APPLICABLE.
- When a live watercourse must be crossed by construction vehicles more than twice in any six-month period, a temporary vehicular stream crossing constructed of nonerodible material shall be provided. NOT APPLICABLE.
- All applicable federal, state and local regulations pertaining to working in or crossing live watercourses shall be met. NOT APPLICABLE.
- The bed and banks of a watercourse shall be stabilized immediately after work in the watercourse is completed. NOT APPLICABLE.
- Underground utility lines shall be installed in accordance with the following standards in addition to other applicable criteria: SEE PLANS FOR PROPOSED UTILITY LOCATIONS COORDINATE WITH APPROPRIATE UTILITY COMPANIES.
 - No more than 500 linear feet of trench may be opened at one time.
 - Excavated material shall be placed on the uphill side of trenches.
 - Effluent from dewatering operations shall be filtered or passed through an approved sediment trapping device, or both, and discharged in a manner that does not adversely affect flowing streams or off-site property.
 - Material used for backfilling trenches shall be properly compacted in order to minimize erosion and promote stabilization.
 - Restoration shall be accomplished in accordance with these regulations.
 - Applicable safety regulations shall be complied with.
- Where construction vehicle access routes intersect paved or public roads, provisions shall be made to minimize the transport of sediment by vehicular loading onto the paved surface. When sediment is transported onto a paved or public road surface, the road surface shall be cleaned thoroughly at the end of each day. Sediment shall be removed from the roads by shoveling or sweeping and transported to a sediment control disposal area. Street washing shall be allowed only after sediment is removed in this manner. This provision shall apply to individual development lots as well as to larger land-disturbing activities. PREVENT DEBRIS FROM ENTERING PETERS CREEK ROAD.
- All temporary erosion and sediment control measures shall be removed within 30 days after final site stabilization or after the temporary measures are no longer needed, unless otherwise authorized by the local program authority. Trapped sediment and the disturbed soil areas resulting from the disposition of temporary measures shall be permanently stabilized to prevent further erosion and sedimentation. CONTACT ROANOKE COUNTY PRIOR TO REMOVING MEASURES.
- Properties and waterways downstream from development sites shall be protected from sediment deposition, erosion and damage due to increases in volume, velocity and peak flow rate of stormwater runoff for the stated frequency storm of 24-hour duration in accordance with the following standards and criteria. AN EXISTING STORMWATER MANAGEMENT FACILITY IS IN PLACE. DRAINAGE STRUCTURES ARE SHOWN ON PLANS.
 - Concentrated stormwater runoff leaving a development site shall be discharged directly into an adequate natural or man-made receiving channel, pipe or storm sewer system. For those sites where runoff is discharged into a pipe or pipe system, downstream stability analyses at the outfall of the pipe or pipe system shall be performed.
 - Adequacy of all channels and pipes shall be verified in the following manner:
 - The applicant shall demonstrate that the total drainage area to a point of analysis within the channel is one hundred times greater than the contributing drainage area of the project in question; or
 - Natural channels shall be analyzed by the use of a two-year storm to verify that stormwater will not overtop channel banks nor cause erosion of channel bed or banks; and
 - All previously constructed man-made channels shall be analyzed by the use of a ten-year storm to verify that stormwater will not overtop its banks and by the use of a two-year storm to demonstrate that stormwater will not cause erosion of channel bed or banks; and
 - Pipes and storm sewer systems shall be analyzed by the use of a ten-year storm to verify that stormwater will be contained within the pipe or system.
- If existing natural receiving channels or previously constructed man-made channels or pipes are not adequate, the applicant shall:
 - Improve the channel to a condition where a ten-year storm will not overtop the banks and a two-year storm will not cause erosion to the channel bed or banks; or
 - Improve the pipe or pipe system to a condition where the ten-year storm is contained within the appurtenances; or
 - Develop a site design that will not cause the pre-development peak runoff rate from a two-year storm to increase when runoff outfalls into a natural channel or will not cause the re-development peak runoff rate from a ten-year storm to increase when runoff outfalls into a man-made channel; or
 - Provide a combination of channel improvement, stormwater detention or other measures which is satisfactory to the plan-approving authority to prevent downstream erosion.
- The applicant shall provide evidence of permission to make the improvements.
- All hydrologic analyses shall be based on the existing watershed characteristics and the ultimate development of the subject project.
- If the applicant chooses an option that includes stormwater detention he shall obtain approval from the locality of a plan for maintenance of the detention facilities. The plan shall set forth the maintenance requirements of the facility and the person responsible for performing the maintenance.
- Outfall from a detention facility shall be discharged to a receiving channel, and energy dissipators shall be placed at the outfall of all detention facilities as necessary to provide a stabilized transition from the facility to the receiving channel.
- All on-site channels must be verified to be adequate.
- Increased volumes of sheet flows that may cause erosion or sedimentation on adjacent property shall be diverted to a stable outlet, adequate channel, pipe or pipe system, or to a detention facility.
- In applying these stormwater runoff criteria, individual lots or parcels in a residential, commercial or industrial development shall not be considered to be separate development projects. Instead, the development, as a whole, shall be considered to be a single development project. Hydrologic parameters that reflect the ultimate development condition shall be used in all engineering calculations.
- All measures used to protect properties and waterways shall be employed in a manner which minimizes impacts on the physical, chemical and biological integrity of rivers, streams and other waters of the state.



ENGINEERING CONCEPTS, INC.

3433 BRAMBLETON AVENUE, SUITE 200B
ROANOKE, VIRGINIA 24018
540.776.5715 FAX: 540.776.8543



No.	Revision	By	Appd.	Date	Drawn
1	REV. PER CO. COMMENTS 7/25/05	DRB	JDE	8-23-05	Designed DRB
2	CO. 9-7-05, CITY 9-1-05 COM.	DRB	JDE	9-26-05	DRB
					Checked JDE
					Approved JDE

ORTHODONTIST OFFICE FOR
PAUL C. KAISER LTD.

DRAINAGE CALCULATIONS
ROANOKE COUNTY, VIRGINIA

WWW.ID# 6PH40

AS SHOWN

JULY 7, 2005

PROJECT: 05050

10