



1. AREAS TO BE GRADED SHALL BE CLEARED AND GRUBBED OF ALL VEGETATION, STRUCTURES, AND OTHER PHYSICAL FEATURES IN PREPARATION OF GRADINGS.
2. TOPSOIL SHALL BE REMOVED FROM THE CLEARED AREA AND STOCKPILED FOR FUTURE USE.
3. FILL MATERIAL SHALL BE FREE OF ORGANIC MATTER AND ROCKS LARGER THAN 6 INCHES IN DIAMETER. FILL MATERIAL SHALL BE PLACED IN 8 INCH LIFTS TO 95% MINIMUM DENSITY, STANDARD PROCTOR.
4. THE OWNER DESERVES THE RIGHT TO TEST THE COMPACTION DENSITY OF FILL MATERIAL.
5. TOPSOIL SHALL BE SPREAD IN A 4 INCH LAYER OVER NON-BUILDING AREAS.
6. THE LOCATION OF ALL OFF-SITE FILL OR BORROW AREAS ASSOCIATED WITH THE PROPOSED CONSTRUCTION PROJECT WILL BE PROVIDED TO THE ROANKE COUNTY COMMUNITY DEVELOPMENT DEPARTMENT. AN EROSION CONTROL PLAN OR MEASURES MAY BE REQUIRED FOR THESE AREAS.

**NORTH VALLEY
SEVENTH DAY ADVENTIST
PREPARED FOR
STRUCTURES DESIGN/BUILD
CATAWBA MAGISTERIAL DISTRICT
ROANOKE COUNTY, VIRGINIA**

REVIEWS		DESCRIPTION
NO.	DATE	
1		
2		
3		
4		
5		

DATE: JUNE 1, 2004

SCALE: NONE

COMMISSION NO: 03-360

CADD FILE: P:\X2533\03360\END\360COMP

SHEET 4 OF 10