QUANTITY + COST ESTIMATE

!TEM	QUANTITY	UNIT	UNIT PRICE	COST	BONDAE
					· · · · · · · · · · · · · · · · · · ·
					,
	· · · · · · · · · · · · · · · · · · ·				
CURB INLET DI-3	10	EACH	\$ 1,500.00	\$ 15,000.00	
DI-7 W/ TYPE III GRATE	4	EACH	\$ 1,200.00	\$ 4,800.00	
SDMH	1	EACH	\$ 1,200.00	\$ 1,200.00	
5-IN. STORM DRAIN, CONC.	391	LIN. FT.	\$ 21.00	\$ 8,211.00	
8-IN. STORM DRAIN, CONC.	448	LIN. FT.	\$ 24.00	\$ 10,752.00	-
24-IN. STORM DRAIN, CONC.	166	LIN. FT.	\$ 30.00	\$ 4,980.00	<u> </u>
24-IN. STORM DRAIN, CMP	15	LIN. FT.	· · · · · · · · · · · · · · · · · · ·	\$ 390.00	·
	27		\$ 26.00	·	
30-IN. STORM DRAIN, CMP	21	LIN. FT.	\$ 32.00	\$ 864.00	<u> </u>
			<u> </u>	 	<u> </u>
NDIVIDUAL SWM UNIT (LOTS 4, 5, &6)	3	EA	\$ 1,000.00	\$ 3,000.00	
			<u> </u>	1	
	·				
		<u> </u>	<u> </u>	 	
				 	 _
MAIN CONC EW-1 MOD W/ ENERGY DISCIR	1	EAGL	₫ 4 000 CC	\$ 1 000 00	
4-IN. CONC. EW-1 , MOD. W/ ENERGY DISSIP.	1	EACH	\$ 1,000.00	\$ 1,000.00	
					<u> </u>
			ļ		
		<u> </u>			
				ļ	
IEADER CURB & GUTTER CG-6	1715	LIN. FT.	\$ 11.00	\$ 18,865.00	
	_				
	1				
	——		<u> </u>		
		 			
			 		
2-IN. SM-9.5A ASPH. CONCRETE PAVING	2,825	S.Y.	\$ 4.00	\$ 11,300.00	
Z III. Ciri D.O. A.C. III. GOITOALIL		0.1.	4 100	7 11,000.00	
		· ·,_ · · · ·			 _
R_IN ACCRECATE BASE #21B STONE	2,825	S.Y.	\$ 5.00	\$ 14,125.00	
8-IN. AGGREGATE BASE #21B STONE	2,020	3.1.	₩ 5.00	\$ 14,125.00	
INOLE WATER METER	3	EACH	# 500 00	A 500.00	
SINGLE WATER METER		<u> </u>	\$ 500.00	\$ 1,500.00	 -
OUBLE WATER METER	3	EACH	\$ 700.00	\$ 2,100.00	
" DUCTILE IRON WATER LINE	254	LIN. FT.	\$ 18.00	\$ 4,572.00	
" C-900 WATER LINE	601	LIN. FT.	\$ 14.00	\$ 8,414.00	
IRE HYDRANT ASSEMBLIES	1	EACH	\$ 1,500.00	\$ 1,500.00	
ERM. END OF WATER LINE ASSY.	1	EACH	\$700.00	\$700.00	
IN. GATE VALVE, W/ CC VAULT, FRAME & COV.	2	EACH	\$ 700.00	\$ 1,400.00	
				_ 	
" SANITARY SEWER	497	LIN. FT.	\$ 20.00	\$ 9,940.00	
" SAN. SEWER LATERAL, CLEANOUT	3	EACH	\$ 300.00	\$ 900.00	
" X (2) 4" SAN. SEWER LATERAL, CLEANOUT	3	EACH	\$ 500.00	\$ 1,500.00	
TANDARD MANHOLE W/FRAME & COVER	2	EACH	\$ 1,200.00	\$ 2,400.00	
WASSING MUNITORN WALLESTER OF ACTION		<u> </u>	# 1,200,00	¥ 2,700.00	· ·
		<u></u>	 	 	
I		 		 	
			ļ	 	····
			ſ		
		<u> </u>	·		
					
TORMWATER MANAGEMENT	1	LUMP SUM	\$ 10,000.00	\$ 10,000.00	
TORMWATER MANAGEMENT	1	LUMP SUM	\$ 10,000.00	\$ 10,000.00	
TORMWATER MANAGEMENT	1	LUMP SUM	\$ 10,000.00	\$ 10,000.00	
TORMWATER MANAGEMENT	1	LUMP SUM	\$ 10,000.00	\$ 10,000.00	
TORMWATER MANAGEMENT	1	LUMP SUM	\$ 10,000.00	\$ 10,000.00	
	1	LUMP SUM	\$ 10,000.00		
TORMWATER MANAGEMENT UBTOTAL O% CONTINGENCY	1	LUMP SUM	\$ 10,000.00	\$ 139,413.00	
UBTOTAL D% CONTINGENCY	1	LUMP SUM		\$ 139,413.00 \$ 13,987.00	
UBTOTAL	1	LUMP SUM		\$ 139,413.00	
UBTOTAL D% CONTINGENCY	1	LUMP SUM		\$ 139,413.00 \$ 13,987.00	

GENERAL NOTES

All construction methods and materials shall conform to the Construction Standards and Specifications of The Western Virginia Water Authority, Roanoke County, and/or the Virginia Department of Transportation.

The contractor or developer is required to notify the Roanoke County Engineering Division and the Western Virginia Water Authority in writing at least three (3) days prior to construction, including but not limited to the following:

- A. Installation of approved erosion control devices
- B. Clearing and grubbing C. Subgrade excavation
- D. Installing storm sewers or culverts
- E. Setting curb and gutter forms
- F. Placing curb and gutter
- G. Placing other concrete
- H. Placing gravel base I. Placing any roadway surface
- J. Installing water lines K. Installing sanitary sewer lines

A pre-construction conference should be scheduled with the Roanoke County Engineering Division, and the Western Virginia Water Authority to be held at least one (1) day prior to any construction.

Measures to control erosion and siltation must be provided prior to plan approval. Plan approval in no way relieves the developer or contractor of the responsibilities contained within the erosion and siltation control policies.

A permit must be obtained from the V.D.O.T. Residency Office, Roanoke County, prior to construction in the highway right-of-way.

Plan approval does not guarantee issuance of any permits by V.D.O.T.

An approved set of plans and all permits must be available at the

Field construction shall honor proposed drainage divides as shown on plans.

All unsuitable material shall be removed from the construction limits of the roadway before placing embankment.

Pavement sections on approved plans are based on a minimum CBR of 10. CBR tests are to be performed by the engineer and submitted to V.D.O.T. and to the Roanoke County Engineering Division prior to placement. CBR values < 10 will require revised pavement sections.

All roadside ditches or grades of more than 5 percent shall be paved with cement concrete to the limits as indicated on the plans and as required at the field inspection.

Location of guard rails shall be determined at a joint field inspection by the County and V.D.O.T.

All springs shall be capped and piped to the nearest storm sewer or natural watercourse. The pipe shall be 6 inch minimum diameter and conform to V.D.O.T. Standard SB-1.

Standard street and traffic control signs shall be erected at each intersection by the developer prior to final street acceptance.

Construction debris shall be containerized in accordance with the Virginia Litter Control Act. No less than one litter receptacle shall be provided on site.

The contractor shall provide adequate means of cleaning mud from trucks and/or other equipment prior to entering public streets. It is the contractors responsibility to insure that the streets are in a clean, mud and dust free condition at all times.

The developer and/or contractor shall supply all utility companies with copies of approved plans, advising them that all grading and installation shall conform to approved plans.

Contractors shall notify utilities of proposed construction at least two (2), but not more than ten (10) working days in advance. Area public utilities may be notified thru "Miss Utility": 1—800—552—7001.

The developer or contractor shall supply the County, and the Western Virginia Water Authority with correct As-Built plans before tentative acceptance.

All work shall be subject to inspection by the Western Virginia Water Authority, Roanoke County, and/or Virginia Department Of Transportation

Field corrections shall be approved by the Roanoke County Engineering Division and the Western Virginia Water Authority prior to such construction.

100 year floodway and floodplain information shall be shown where

Grade stakes shall be set for all curb and gutter, culvert, sanitary sewer and storm sewer.

INDEX

see lumsden associates, P.C. Cover sheet

SEWER NOTES

All sanitary sewer connections to existing lines shall be coordinated with and performed by the Western Virginia Water Authority.

All water and sanitary sewer facilities are to be installed according to Western Virginia Water Authority Design and Construction Standards.

A minimum cover of three (3) feet is required over proposed lines.

Contractor shall be responsible for locating and uncovering all manholes after paving. Manhole tops shall be adjusted to grade if necessary.

All existing utilities may not be shown or may not be shown in the exact location. The contractor shall comply with State Water Works Regulations, Section 12.05.03, where lines cross.

House connections are to be made with 4" pipe installed at a minimum grade of 1/4 inch to 1 foot in R/W.

Laterals from manholes shall be PVC or Ductile Iron of sufficient length to provide two (2) feet of bearing on natural ground. The transition from ductile iron to asbestos cement or concrete pipe shall be made with an adapter coupling in R/W.

All trenches in existing or future rights—of—way shall be compacted according to V.D.O.T. standards.

Lines shall be staked prior to construction.

WATER NOTES

All water connections to existing lines will be coordinated with and performed by the Western Virginia Water Authority.

All water and sanitary sewer facilities are to be installed according to Western Virginia Water Authority Design and Construction Standards. A minimum cover of three (3) feet is required over proposed lines.

Contractor shall be responsible for locating and uncovering valve vaults after paving and adjustment to final grade if necessary,

All existing utilities may not be shown or may not be shown in the exact location. The contractor shall comply with the State Water Works Regulations, Section 12.05.03, where lines cross.

All trenches in existing or future highway right-of-ways shall be compacted according to V.D.O.T. standards.

Lines shall be staked prior to construction.

Water main shall be minimum Class 350 Ductile Iron in accordance to AWWA C150 or DR-14 PVC in accordance with AWWA C-900.

Availability number _____

	LEGEND
Property Line	
Right-of-way	· · R/W · · · ·
Centerline	
Minimum Building Line	
Existing Storm Sewer	18" S.D18" S.D
Existing Sanitary Sewer	8" SAN. ====================================
Existing Water Main	
Existing Contour	
Proposed Contour	1045
Proposed Drainage Divide	
Proposed Limits of Clearing	
Proposed Storm Sewer	24" S.D.
Proposed Sanitary Sewer	8" M.H.
Proposed Water Main	HYDRANT X VALVE BLOWOFF

SURVEY INFORMATION

VICINITY MAP

see lunsden associates, p.C. cover sheet


tal	and	vertical	control	surveys	were	performed	in	(year)_	2004
LUMSDEN ASSOCIATES, P.C.									

All elevations must be referenced to the National Geodetic Vertical Datum of 1929.

Source of topographic mapping is	SURVEY PERFORMED BY LUMSDEN ASSOCIATES, P.C.
dated MAY 2004	

Boundary was performed by LUMSDEN ASSOCIATES, P.C.

The professional seal and signature below certifies the boundary survey and topographic mapping to be accurate and correct.



PROFESSIONAL SEAL AND SIGNATURE

COUNTY OF ROANOKE

NAME OF DEVELOPMENT	77UE GËAFDME	I,OWNE
	"The reserve"	OF THE SITE DESIGN RE
		THIS SITE DEVELOPMENT
		LICABLE COUNTY CODES
MAGISTERIAL DISTRICT(S)	Windsor Hills	I AGREE TO COMPLY WI

ER/DEVELOPER, AM AWARE EQUIREMENTS IMPOSED BY T PLAN AND OTHER APP-S. I HEREBY CERTIFY THAT I AGREE TO COMPLY WITH THESE REQUIREMENTS. UNLESS MODIFIED IN ACCORDANCE WITH LOCAL LAW.

OWNER (name, address, telephone)

TAX MAP NO(S)

GEORGE P. BARON, JR. 2111 CHESTNUT OAK COURT ROANOKE, VIRGINIA 24018

15401 989-7646

DEVELOPER (name, address, telephone) SEE OWNER

Lumsden associates, P.C. ENGINEER, ARCHITECT OR SURVEYOR (name, address, telephone) P.O. BOX 20669

ROANOKE, VIRGINIA 24018

BLOCK NO(S)

15401 774-4411

PARCEL NO(S)

COMM: 2004-026

SHEET 2 OF 11