QUANTITY + COST ESTIMATE

ITEM	QUANTIT	/ UNIT	UNIT PRICE	COST	BONDAB
8" SANITARY SEWER	438	LIN. FT.	\$ 20.00	\$ 8,760.00	
STANDARD MANHOLE W/FRAME & COVER	4	EACH	\$ 1,200.00	\$ 4,800.00	
OUTSIDE DROP/STRADDLE MH	1	EACH	\$ 2,000.00	\$ 2,000.00	
					····
					-
					
		 	<u> </u>		
					<u> </u>
				<u> </u>	
		_			<u> </u>
·····					
			<u> </u>		<u> </u>
	·-···.				
					<u>. </u>
				<u> </u>	<u> </u>
		_			
			 	<u> </u>	
	*				
CURTOTAL				A 45 = 55 55	
SUBTOTAL 10% CONTINGENCY				\$ 15,560.00 \$ 1,560.00	
ESTIMATED TOTAL				\$ 17,120.00	<u> </u>
					<u></u>

GENERAL NOTES

All construction methods and materials shall conform to the Construction Standards and Specifications of The Western Virginia Water Authority. Roanoke County, and/or the Virginia Department of Transportation.

The contractor or developer is required to notify the Roanoke County Engineering Division and the Western Virginia Water Authority in writing at least three (3) days prior to construction, including but not limited to the following:

- A. Installation of approved erosion control devices
- B. Clearing and grubbing C. Subgrade excavation
- D. Installing storm sewers or culverts
- E. Setting curb and gutter forms F. Placing curb and gutter
- G. Placing other concrete
- H. Placing gravel base
- I. Placing any roadway surface
- J. Installing water lines K. Installing sanitary sewer lines

A pre-construction conference should be scheduled with the Rognoke County Engineering Division, and the Western Virginia Water Authority to be held at least one (1) day prior to any construction.

Measures to control erosion and siltation must be provided prior to plan approval. Plan approval in no way relieves the developer or contractor of the responsibilities contained within the erosion and siltation control policies.

A permit must be obtained from the V.D.O.T. Residency Office, Roanoke County, prior to construction in the highway right-of-way.

Plan approval does not guarantee issuance of any permits by V.D.O.T.

An approved set of plans and all permits must be available at the construction site.

Field construction shall honor proposed drainage divides as shown

All unsuitable material shall be removed from the construction limits of the roadway before placing embankment.

Pavement sections on approved plans are based on a minimum CBR of 10. CBR tests are to be performed by the engineer and submitted to V.D.O.T. and to the Roanoke County Engineering Division prior to placement. CBR values < 10 will require revised pavement sections.

All roadside ditches or grades of more than 5 percent shall be paved with cement concrete to the limits as indicated on the plans and as required at the field inspection.

Location of guard rails shall be determined at a joint field inspection by the County and V.D.O.T.

All springs shall be capped and piped to the nearest storm sewer or natural watercourse. The pipe shall be 6 inch minimum diameter and conform to V.D.O.T. Standard SB-1.

intersection by the developer prior to final street acceptance. Construction debris shall be containerized in accordance with the

Standard street and traffic control signs shall be erected at each

Virainia Litter Control Act. No less than one litter receptacle shall be provided on site.

The contractor shall provide adequate means of cleaning mud from trucks and/or other equipment prior to entering public streets. It is the contractors responsibility to insure that the streets are in a clean, mud and dust free condition at all times.

The developer and/or contractor shall supply all utility companies with copies of approved plans, advising them that all grading and installation shall conform to approved plans.

Contractors shall notify utilities of proposed construction at least two (2), but not more than ten (10) working days in advance. Area public utilities may be notified thru "Miss Utility": 1-800-552-7001.

The developer or contractor shall supply the County, and the Western Virginia Water Authority with correct As—Built plans before tentative acceptance.

All work shall be subject to inspection by the Western Virginia Water Authority, Roanoke County, and/or Virginia Department Of Transportation

Field corrections shall be approved by the Roanoke County Engineering Division and the Western Virginia Water Authority prior to such construction. 100 year floodway and floodplain information shall be shown where

applicable. Grade stakes shall be set for all curb and gutter, culvert, sanitary sewer and storm sewer.

INDEX

SEE LUMSDEN ASSOCIATES, P.C. COVER SHEET

SEWER NOTES

All sanitary sewer connections to existing lines shall be coordinated with and performed by the Western Virginia Water Authority.

All water and sanitary sewer facilities are to be installed according to Western Virginia Water Authority Design and Construction Standards.

A minimum cover of three (3) feet is required over proposed lines.

Contractor shall be responsible for locating and uncovering all manholes after paving. Manhole tops shall be adjusted to grade if necessary.

All existing utilities may not be shown or may not be shown in the exact location. The contractor shall comply with State Water Works Regulations, Section 12.05.03, where lines cross.

House connections are to be made with 4" pipe installed at a minimum grade of 1/4 inch to 1 foot in R/W.

Laterals from manholes shall be PVC or Ductile Iron of sufficient length to provide two (2) feet of bearing on natural ground. The transition from ductile iron to asbestos cement or concrete pipe shall be made with an adapter coupling in R/W.

All trenches in existing or future rights-of-way shall be compacted according to V.D.O.T. standards.

Lines shall be staked prior to construction.

WATER NOTES

All water connections to existing lines will be coordinated with and performed by the Western Virginia Water Authority. All water and sanitary sewer facilities are to be installed according to Western Virginia Water Authority Design and Construction Standards.

Contractor shall be responsible for locating and uncovering valve vaults after paving and adjustment to final grade if necessary.

A minimum cover of three (3) feet is required over proposed lines.

All existing utilities may not be shown or may not be shown in the exact location. The contractor shall comply with the State Water Works Regulations, Section 12.05.03, where lines cross.

All trenches in existing or future highway right—of—ways shall be compacted according to V.D.O.T. standards.

Lines shall be staked prior to construction.

Water main shall be minimum Class 52 Ductile Iron in accordance to AWWA C151 or DR-14 PVC in accordance with AWWA C-900.

Availability number _____

LEGEND

Right-of-way Centerline Minimum Building Line

Existing Storm Sewer Existing Sanitary Sewer

Existing Water Main Existing Contour

Property Line

Proposed Contour Proposed Drainage Divide

Proposed Limits of Clearing Proposed Storm Sewer

Proposed Sanitary Sewe Proposed Water Main

SEE LUMSDEN ASSOCIATES, P.C. COVER SHEET

VICINITY MAP

SURVEY INFORMATION


Horizontal and vertical control surveys were performed in (year) _______2004 LUMSDEN ASSOCIATES, P.C.

All elevations must be referenced to the National Geodetic Vertical Datum of 1929.

Source of topographic mapping is_____ SURVEY PERFORMED BY LUMSDEN ASSOCIATES, P.C. dated <u>NOVEMBER 2004</u>

Boundary was performed by _____ LUMSDEN ASSOCIATES, P.C. dated ____ NOVEMBER 2004

The professional seal and signature below certifies the boundary survey and topographic mapping to be accurate and correct.



PROFESSIONAL SEAL AND SIGNATURE

COUNTY OF ROANOKE

SANITARY SEWER EXTENSION FOR NAME OF DEVELOPMENT FUTURE DEVELOPMENT

MAGISTERIAL DISTRICT(S)

WINDSOR HILLS

66.04

OWNER/DEVELOPER, AM AWARE OF THE SITE DESIGN REQUIREMENTS IMPOSED BY THIS SITE DEVELOPMENT PLAN AND OTHER APP-LICABLE COUNTY CODES. I HEREBY CERTIFY THAT I AGREE TO COMPLY WITH THESE REQUIREMENTS. UNLESS MODIFIED IN ACCORDANCE WITH LOCAL LAW.

OWNER (name, address, telephone)

TAX MAP NO(S)

BARON ENTERPRISES 2111 CHESTNUT OAK COURT **ROANOKE, VIRGINIA 24018**

15401 989-7646

01

DEVELOPER (name, address, telephone)

SEE OWNER

ENGINEER, ARCHITECT OR SURVEYOR (name, address, telephone)

P.O. BOX 20669 ROANOKE, VIRGINIA 24018

LUMSDEN ASSOCIATES, P.C.

15401 774-4411

PARCEL NO(S)

BLOCK NO(S)

SHEET 2 OF 7