GENERAL NOTES

- PRE-CONSTRUCTION MEETING AND CONSTRUCTION COMMENCEMENT:
- 1. All construction methods and materials shall conform to the Construction Standards and Specifications of Roanoke County, the Western Virginia Water Authority, and the Virginia Department of Transportation.
- 2. Stormwater Management Agreements with an attached 8 1/2" x 11" or 8 1/2" x 14" plat must be approved and recorded prior to the pre-construction meeting.
- 3. Once all required items are submitted to the County of Roanoke, the developer must contact the Development Review Coordinator to indicate that a pre-construction meeting needs to be scheduled. The pre-construction meeting will be scheduled with the owner/developer two (2) working days later.
- 4. All land disturbing projects that require approval of an erosion and sediment control plan, grading or clearing permit shall require that the applicant provide the name of an individual who will be responsible for land disturbing activities and that this individual hold a Responsible Land Disturber (RLD) Certificate from the Department of Environmental Quality. The Responsible Land Disturber can be anyone from the Project team that is certified by the Commonwealth of Virginia to be in charge of carrying out the land disturbing activity for the project.
- 5. It is the responsibility of the owner/developer to notify the certified Responsible Land Disturber and the Utility Contractor to attend the pre-construction meeting.
- 6. The Development Review Coordinator will schedule the pre-construction meeting with the County Review Engineer, the County Inspector, and the Western Virginia Water Authority and the Town of Vinton Public Works Department if applicable.
- 7. An approved set of plans, Storm Water Pollution Prevention Plan (SWPPP), VSMP coverage letter, and all permits must be available at the construction site at all times.
- 8. The developer and/or contractor shall supply all utility companies with copies of approved plans, advising them that all grading and installation shall conform to approved plans.
- 9. The project engineer will inform the owner/developer verbally and in writing of the County's obligation to perform inspections on site. Everyone in the meeting will be required to sign a pre-construction checklist indicating their knowledge of Roanoke County's obligation to perform inspections on site.
- 10. The Erosion Control Permit or Combined Erosion Control & VSMP Permit is given to the developer at this pre-construction meeting.
- 11. Notify the County of Roanoke prior to beginning installation of ESC measures. The County will inspect initial installations to ensure compliance with approved plan prior to start of grading. The developer SHALL contact the project inspector 24 hours before beginning any grading or construction on the property.
- 12. County inspectors must inspect storm drain / stormwater management / BMP installations during the process of installation. Please contact the site inspector 24 hours in advance.
- 13. All work shall be subject to inspection by Roanoke County, the Western Virginia Water Authority and the Virginia Department of Transportation Inspectors.
- 14. Contractors shall notify utilities of proposed construction at least two (2), but not more than ten (10) working days in advance. Area public utilities may be notified thru "Miss Utility": 1-800-552-7001 or VA 811
- 15. The 100 year Floodway shall be staked prior to any construction.
- 16. Grade stakes shall be set for all curb and gutter, culvert, sanitary sewer and storm sewer at all times of construction.
- 17. The Department of Community Development shall be notified when a spring is encountered during construction.
- 18. Construction debris shall be containerized in accordance with the Virginia Litter Control Act. No less than one litter receptacle shall be provided on site.
- 19. The contractor shall provide adequate means of cleaning mud from trucks and/or other equipment prior to entering public streets or rights of ways. It is the contractors responsibility to insure that the streets are in a clean, mud and dust free condition at
- 20. Plan approval in no way relieves the developer or contractors of the responsibilities contained within the erosion and sediment control or stormwater management policies.
- 21. Field construction shall honor proposed drainage divides as shown on plans.
- 22. Field corrections shall be approved by the Roanoke County Engineering Division and/or the Western Virginia Water Authority and the Professional of Record, prior to
- 23. The developer or contractor shall supply the County and the Western Virginia Water Authority with correct As-Built plans before final acceptance.


VIRGINIA DEPARTMENT OF TRANSPORTATION:

- 24. Plan approval by Roanoke County does not guarantee issuance of any permits by the Virginia Department of Transportation.
- 25. A permit must be obtained from the Virginia Department of Transportation, Salem Residency Office prior to construction in the highway right-of-way.
- 26. The preliminary pavement designs should be based on a predicted sub-grade CBR value of 7.0 and with a Resiliency Factor (RF) of 2.0 as shown in Appendix I of the 2000 Virginia Department of Transportation Pavement Design Guide for Subdivision and Secondary Roads. The sub-grade soil is to be tested by an independent laboratory and the results submitted to the Virginia Department of Transportation prior to base construction. Should the sub-grade CBR value and/or the RF value be less than the predicted values, additional base material will be required in accordance with Departmental specifications. Refer to the same manual as the number and locations of the required soil samples to be tested. All pavement designs shall be submitted to the Department for review and approval. The sub-grade shall be approved by the Virginia Department of Transportation prior to placement of the base. Base shall be approved by the Virginia Department of Transportation for depth, template, and compaction before the surface is applied.
- 27. Standard guardrail with safety end sections may be required on fills or in areas where hazards exist as deemed necessary. After completion of rough grading operations, the County Engineer and Virginia Department of Transportation shall be contacted to schedule a field review. Where guard rail is warranted, the standard shoulder width shall be provided and the guard rail shall be installed in accordance with the 2001 VDOT Road and Bridge Standards as part of this development.
- 28. Standard street and traffic control signs shall be erected at each intersection by the developer prior to final street acceptance.
- 29. All traffic devices shall be in accordance with current edition of the "Manual on Uniform Traffic Control Devices" (MUTCD).
- 30. All unsuitable material shall be removed from the construction limits of the roadway before placing embankment.

See Sheet N/A for Stormwater Site Statistics Table. See Sheet N/A for New BMP Information Table.

The Project Engineer shall provide electronic copies of the approved plans to the Development Review Coordinator within 5 working days of the pre-construction

The notes on this sheet shall not be modified.



COUNTY OF ROANOKE, VA

NAME OF DEVELOPMENT PUMP STATION AND FORCE MAIN Tax Map No. 080.00-05-04.00	OWNER/DEVELOPER, AM AWARE OF THE SITE DESIGN REQUIREMENTS IMPOSED BY THIS SITE DEVELOPMENT PLAN AND OTHER APPLICABLE ROANOKE COUNTY CODES.
MAGISTERIAL DISTRICT	I HEREBY CERTIFY THAT I AGREE TO COMPLY WITH THESE REQUIREMENTS AND THE THIRTY (30) POINTS SHOWN ON THIS COVER SHEET UNLESS MODIFIED IN ACCORDANCE WITH LOCAL LAW.
OWNER (name, address, telephone) ROANOKE VALLEY RESOURCE AUTHORITY	1020 HOLLINS ROAD, N.E. ROANOKE, VA 24012
DEVELOPER (name, address, telephone) ROANOKE VALLEY RESOURCE AUTHORITY	1020 HOLLINS ROAD, N.E. ROANOKE, VA 24012
ENGINEER, ARCHITECT OR SURVEYOR (name, address, telephone) GEOSYNTEC CONSULTAN (804) 767-2206	9211 ARBORETUM PARKWAY, SUITE 200 RICHMOND, VIRGINIA 23236
TAX MAP NO(S) 080.00-05-04.00	

WATER NOTES

All water facilities shall be constructed according to the Western Virginia Regional Design and Construction Standards (Latest Edition).

A minimum cover of three (3) feet is required over proposed lines.

Contractor shall be responsible for locating and uncovering valve

vaults after paving and adjustment to final grade if necessary.

All existing utilities may not be shown in their exact location. The contractor shall comply with the (State Water Works Regulations, Section 12VAC5-590-1150, where lines cross.

All trenches in existing or future highway right-of-ways shall be compacted according to Virginia Department of Transportation


Lines shall be staked prior to construction.

standards.

Water main shall be minimum Class 350 Ductile Iron in accordance to AWWA C151 or DR-14 PVC in accordance with AWWA C-900.

Ductile Iron Pipe in accordance with the Western Virginia Regional Design and Construction Standards shall be required for all pipe with a working pressure equal to or greater than 100 p.s.i.

Western Virginia Water Authority Availability letter number:



manuscramental OHD man manuscramental	OHU	EXISTING OVERHEAD POWER
		EXISTING PROPERTY LINE
. A STATE OF THE S		EXISTING ROAD - ASPHALT
TOCASCALAR ANCINTOCA (ANCINTAN) ANTITOCAN ANTITOCAN SUPPLINOS SUPPLINOS SUPPLINOS	a andiana shifting distinguis	EXISTING ROAD - GRAVEL
	B SANGERSANDERSON	EXISTING STORM PIPE
annonament in internation was a second of the second of th	And the analysis of the analys	EXISTING CONTOUR
>		EXISTING GUY WIRE
ಌ		EXISTING POWER POLE
		EXISTING LANDFILL LIMITS
rangerimmunicament fC angelini masaminini fC	* ************************************	EXISTING LEACHATE PIPE
management G management G management	— G ——	EXISTING LANDFILL GAS LINE
SD SD		EXISTING SLOPE DRAIN
		STORM PIPE BY OTHERS
FM FM	1	PROPOSED FORCE MAIN
		PROPOSED TRENCH PROTECTION
LCLC		PROPOSED LEACHATE COLLECTION PIPE
1034		PROPOSED CONTOUR
	UG	ELECTRICAL AND COMMUNICATIONS CONDUITS
	-	DRAINAGE FLOW
LOD L	.OD ——	LIMITS OF DISTURBANCE

2" NO. 25 OR 26 STONE

LEGEND

SEWER NOTES

All sanitary sewer facilities shall be installed according to the Western Virginia Regional Design and Construction Standards. (Latest Edition).

A minimum cover of three (3) feet is required over proposed lines. Contractor shall be responsible for locating and uncovering all manholes after paving. Manhole tops shall be adjusted to grade if necessary.

All existing utilities may not be shown in their exact location. The contractor shall comply with (State Water Works Regulations, Section 12VAC5-590-1150, where

All trenches in existing or future rights-of-way shall be compacted according to Virginia Department of Transportation standards. Lines shall be staked prior to construction.

PRIVATE UTILITIES

Underground utilities installed on private property or in private utility easements and building related storm drains shall be designed and installed per the current edition of the Virginia Uniform Statewide Building Code. Design and installation requirements issued by the Western Virginia Water Authority that meet or exceed the USBC requirements are acceptable for private utilities. All private utilities are to be permitted through and inspected by the Roanoke County Inspections Office. Vaults, valves and other devices installed by or under the control of the Western Virginia Water Authority may not substituted for the code required devices.

CENT OF MANAGEMENT OF THE CONTROL OF	DRAWING NO.	DRAWING TITLE
Y Niagara	1	ROANOKE COUNTY COVER SHEET
Niagara Solo Solo Solo Solo Solo Solo Solo Sol	2	COVER SHEET
Resident	3	OVERVIEW PLAN AND GENERAL NOTES
1000	4	EROSION & SEDIMENT CONTROL NARRATIVE
Roanoke-River	5	EROSION & SEDIMENT CONTROL MINIMUM STANDARDS
	6	PLAN AND PROFILE - EROSION AND SEDIMENT CONTROL 1 OF 3
O RO	7	PLAN AND PROFILE - EROSION AND SEDIMENT CONTROL 2 OF 3
BLUERIDGE PARKWAY,	8	PLAN AND PROFILE - EROSION AND SEDIMENT CONTROL 3 OF 3
	9	PUMP STATION PLAN
	10	CONSTRUCTION DETAILS 1 OF 3
	11	CONSTRUCTION DETAILS 2 OF 3
	12	CONSTRUCTION DETAILS 3 OF 3
Vicinity Map	13	ELECTRICAL PLAN AND DETAILS
	14	PUMP CALCULATIONS

SURVEY INFORMATION

Sheet Index

By: Lumso	len Associates, P.	<u>ن.</u>			
					ertical Datum of 1929 or 1 atum of 1927 or 1983.
Horizontal Da	atum <u>:</u> Lumsden As	sociates, P.C. Ver	tical Datun	n: Lums	den Associates, P.C.
Source of top	ographic mapping	is dated Field Sur	vey by Lui	msden A	ssociates, P.C. in 2016
Boundary wa	s performed by Lu	umsden Associates	s, P.C.	dated: _	2016
0	nformation: N/A				

The professional seal and signature certifies the boundary survey and topographic mapping to be accurate and correct.

ITEM	QUANTITY	UNIT	UNIT PRICE	COST	BONDABLE
CLEARING AND GRUBBING		AC			
EXCAVATION		C.Y.			
EMBANKMENT		C.Y.			
CURB INLET DI-		EA			
CURB INLET DI-		EA			
					·
ESTIMATED TOTAL					


BY SEALING THE PLANS, THE DESIGN PROFESSIONAL HEREBY CERTIFIES THAT THE FOREGOING ESTIMATE REFLECTS THE CURRENT IMPROVEMENT COSTS OF THIS PROJECT.

OLIANITITY & COST ESTIMATE

2 **7**







dfill ain Z a ugh Ro

on on Rutr Stati

d

SHEET