## **GENERAL NOTES**

PRE-CONSTRUCTION MEETING AND CONSTRUCTION COMMENCEMENT:

- 1. All construction methods and materials shall conform to the Construction Standards and Specifications of Roanoke County, the Western Virginia Water Authority, and the Virginia Department of Transportation.
- 2. Stormwater Management Agreements with an attached 8 1/2" x 11" or 8 1/2" x 14" plat must be approved and recorded prior to the pre-construction meeting.
- 3. Once all required items are submitted to the County of Roanoke, the developer must contact the Development Review Coordinator to indicate that a pre-construction meeting needs to be scheduled. The pre-construction meeting will be scheduled with the owner/developer two (2) working days later.
- 4. Please note the 2001 General Assembly revisions to Va Erosion and Sediment Control Law. Effective July 1, 2001, all land disturbing projects that require approval of an erosion and sediment control plan, grading or clearing permit shall require that the applicant provide the name of an individual who will be responsible for land disturbing activities and that this individual hold a Responsible Land Disturber (RLD) Certificate from the Department of Conservation and Recreation. The Responsible Land Disturber can be anyone from the Project team that is certified by the State of Virginia to be in charge of carrying out the land disturbing activity for the project.
- 5. It is the responsibility of the owner/developer to notify the certified Responsible Land Disturber and the Utility Contractor to attend the pre-construction meeting.
- 6. The Development Review Coordinator will schedule the pre-construction meeting with the County Review Engineer, the County Inspector, and the Western Virginia Water Authority and the Town of Vinton Public Works Department if applicable.
- 7. An approved set of plans and all permits <u>must be available</u> at the construction site at all times.
- 8. The developer and/or contractor shall supply all utility companies with copies of approved plans, advising them that all grading and installation shall conform to approved plans.
- 9. The project engineer will inform the owner/developer verbally and in writing of the County's obligation to perform inspections on site. Everyone in the meeting will be required to sign a pre-construction checklist indicating their knowledge of Roanoke County's obligation to perform inspections on site.
- 10. The Erosion Control Permit is given to the developer at this pre-construction meeting.
- 11. The developer MUST contact the project inspector 24 hours before beginning any grading or construction on the property.
- 12. The project inspector will visit the site within 48 hours of the developer's call to ensure that all necessary erosion and sediment control measures are properly installed according to the approved plan.
- 13. All work shall be subject to inspection by Roanoke County, the Western Virginia Water Authority and the Virginia Department of Transportation Inspectors.
- 14. Contractors shall notify utilities of proposed construction at least two (2), but not more than ten (10) working days in advance. Area public utilities may be notified thru "Miss Utility": 1-800-552-7001.
- 15. 100 year Floodway and Floodplain information shall be shown where applicable. FIRM Index Date shall be shown on the plans. The 100 year Floodway shall be staked prior to any construction.
- 16. Grade stakes shall be set for all curb and gutter, culvert, sanitary sewer and
- 17. The Department of Community Development shall be notified when a spring is encountered during construction.
- 18. Construction debris shall be containerized in accordance with the Virginia Litter Control Act. No less than one litter receptacle shall be provided on site.
- 19. The contractor shall provide adequate means of cleaning mud from trucks and/or other equipment prior to entering public streets or rights of ways. It is the contractors responsibility to insure that the streets are in a clean, mud and dust free condition at all times.
- 20. Plan approval in no way relieves the developer or contractors of the responsibilities contained within the erosion and sediment control policies.
- 21. Field construction shall honor proposed drainage divides as shown on plans.
- 22. Field corrections shall be approved by the Roanoke County Engineering Division and/or the Western Virginia Water Authority and the Professional of Record.
- 23. The developer or contractor shall supply the County and the Western Virginia Water Authority with correct As-Built plans before final acceptance.


## VIRGINIA DEPARTMENT OF TRANSPORTATION:

- 24. Plan approval by Roanoke County does not guarantee issuance of any permits by the Virginia Department of Transportation.
- 25. A permit must be obtained from the Virginia Department of Transportation, Salem Residency Office prior to construction in the highway right-of-way.
- 26. The preliminary pavement designs should be based on a predicted sub-grade CDR value of 7.0 and with a Resiliency Factor (RF) of 2.0 as shown in Appendix I of the 2000 Virginia Department of Transportation Pavement Design Guide for Subdivision and Secondary Roads. The sub-grade soil is to be tested by an independent laboratory and the results submitted to the Virginia Department of Transportation prior to base construction. Should the sub-grade CBR value and/or the RF value be less than the predicted values, additional base material will be required in accordance with Departmental specifications. Refer to the same manual as the number and locations of the required soil samples to be tested. All pavement designs shall be submitted to the Department for review and approval. The sub-grade shall be approved by the Virginia Department of Transportation prior to placement of the base. Base shall be approved by the Virginia Department of Transportation for depth, template, and compaction before the surface is applied.
- 27. Standard guardrail with safety end sections may be required on fills or in areas where hazards exist as deemed necessary. After completion of rough grading operations, the County Engineer and Virginia Department of Transportation shall be contacted to schedule a field review. Where guard rail is warranted, the standard shoulder width shall be provided and the guard rail shall be installed in accordance with the 2001 VDOT Road and Bridge Standards as part of this development.
- 28. Standard street and traffic control signs shall be erected at each intersection by the developer prior to final street acceptance.
- 29. All traffic devices shall be in accordance with current edition of the manual: "Uniform Traffic Control Devices (MUTCD)"

This sheet may not be modified.

30. All unsuitable material shall be removed from the construction limits of the roadway before placing embankment.

The Project Engineer shall provide electronic copies of the approved plans to the Development Review Coordinator within 5 working days of the pre-construction meeting.



# County of Roanoke, VA

NAME OF DEVELOPMENT	ST. CLAIR GARDENS	OWNER/DEVELOPER,  AM AWARE OF THE SITE DESIGN REQUIREMENTS IMPOSED BY THIS SITE  DEVELOPMENT PLAN AND OTHER APPLICABLE ROANOKE COUNTY CODES.
MAGISTERIAL DISTRICT(S)	CATAWBA	I HEREBY CERTIFY THAT I AGREE TO COMPLY WITH THESE REQUIREMENTS AND THE THIRTY (30) POINTS SHOWN ON THIS COVER SHEET UNLESS MODIFIED IN ACCORDANCE WITH LOCAL LAW.
OWNER (name, address, telephone)	R. FRALIN DEVELOPMENT CORP. 2404 ELECTRIC RD. SUITE B ROANOKE, VA 24018 (540) 204-4247 ATTN. ROB	ERT FRALIN
DEVELOPER (name, address, telephone)	R. FRALIN DEVELOPMENT CORP. 2404 ELECTRIC RD. SUITE B ROANOKE, VA 24018 (540) 204-4247 ATTN. ROB	ERT FRALIN
ENGINEER, ARCHITECT OR SURVEYOR	BALZER AND ASSOCIATES, INC.  1208 CORPORATE CIRCLE  ROANOKE, VA 24018 (540) 77	2-9580 ATTN: CHRIS BURNS
TAX MAP NO(S)	035.00-01-22.00-0000, 035.00-01-23.00-0000	

### WATER NOTES

All water facilities shall be installed according to the Western Virginia Water Authority Design and Construction Standards/ (Latest Edition).

A minimum cover of three (3) feet is required over proposed lines. Contractor shall be responsible for locating and uncovering valve vaults after paving and adjustment to final grade if necessary.

All existing utilities may not be shown in their exact location. The contractor shall comply with the (State Water Works Regulations, Section 12.05.03, where lines cross.


All trenches in existing or future highway right-of-ways shall be compacted according to Virginia Department of Transportation standards.

Lines shall be staked prior to construction.

Water main shall be minimum Class 350 Ductile Iron in accordance to AWWA C151 or DR-14 PVC in accordance with AWWA C-900.

Ductile Iron Pipe in accordance with the Western Virginia Water Authority Design and Construction Standards shall be required for all pipe with a working pressure equal to or greater than 100 p.s.i.

Western Virginia Water Auth	ority
Availability letter number:	09-1



<u>LEGEND</u>		
Property Line		
Right-of-way		
Centerline		
Minimum Building Line	MBL	
Existing Storm Sewer		
Existing Sanitary Sewer	8" ss	
Existing Water Main	8" w	
Existing Contour	1155	
Proposed Contour		
Proposed Drainage Divide		
Proposed Limits of Clearing		
Proposed Storm Sewer		
Proposed Sanitary Sewer	8" SS	
Proposed Water Main	8" W	
TO BE REMOVED	T.B.R.	

# SEWER NOTES

All sanitary sewer facilities shall be installed according to the Western Virginia Water Authority Design and Construction Standards. (Latest Edition).

A minimum cover of three (3) feet is required over proposed lines.

Contractor shall be responsible for locating and uncovering all manholes after paving. Manhole tops shall be adjusted to grade

according to Virginia Department of Transportation standards.

Lines shall be staked prior to construction.

	SHEET INDEX
C-1	COVER SHEET
C-2	GENERAL NOTES
C-3	EXISTING CONDITIONS & DEMO PLAN
C-3A	OVERALL PLAN
C-4	LAYOUT & UTILITY PLAN
C-5	OVERALL GRADING PLAN
C-6	OFF-SITE UTILITY EXTENSION
C-7	PROFILES
C-8	PHASE I ESC PLAN
C-9	PHASE II ESC PLAN
C-10	ESC NOTES
C-11	ESC DETAILS
C-12	DETAILS
C-13	OVERLOT GRADING PLAN
C-14	WVWA WATER DETAILS
C-15	WVWA SANITARY SEWER DETAILS

## **SURVEY INFORMATION**

Horizontal and vertical control sur By: BALZER AND ASSOC	• • • • • • • • • • • • • • • • • • • •
	to the National Geodetic Vertical Datum of 1988. s are referenced to Roanoke County Deed Book 792, Pg. 69
Source of topographic mapping is	ROANOKE COUNTY G.I.S. dated: 1992
Boundary was performed by:	BALZER AND ASSOCIATES, INC. dated: 2009
	AND ASSOCIATES TRAVERSE POINTS DING PLAN FOR LOCATIONS AND ELEVATIONS

if necessary.

All existing utilities may not be shown in their exact location. The contractor shall comply with (State Water Works Regulations, Section 12.05.03, where lines cross.)

All trenches in existing or future rights-of-way shall be compacted

## PRIVATE UTILITIES

Underground utilities installed on private property or in private utility easements and building related storm drains shall be designed and installed per the current edition of the Virginia Uniform Statewide Building Code. Design and installation requirements issued by the Western Virginia Water Authority that meet or exceed the USBC requirements are acceptable for private utilities. All private utilities are to be permitted through and inspected by the Roanoke County Inspections Office. Vaults, valves and other devices installed by or under the control of the Western Virginia Water Authority may not substituted for the code required devices.

Horizontal and vertical control surveys were performed in year: 2009  By: BALZER AND ASSOCIATES, INC.
Vertical elevations are referenced to the National Geodetic Vertical Datum of 1988.  Horizontal bearings and distances are referenced to Roanoke County Deed Book 792, Pg. 69.
Source of topographic mapping is: ROANOKE COUNTY G.I.S. dated: 1992
Boundary was performed by: BALZER AND ASSOCIATES, INC. dated: 2009
Benchmark Information: BALZER AND ASSOCIATES TRAVERSE POINTS SEE GRADING PLAN FOR LOCATIONS AND ELEVATIONS
The professional seal and signature certifies the boundary survey and topographic mapping to be accurate and correct.

QUANTIT	Y & COS	T ESTIMA	ATE		`
ITEM	QUANTITY	UNIT	UNIT PRICE	COST	BONDABLE
CLEARING AND GRUBBING	••	ACRES	\$		\$
GRADING - ROADWAYS ONLY	••	C.Y.	\$		\$
DEMOLITION		LUMP SUM	\$		\$
GRATE INLET DI-1 SERIES	1	EACH	\$ 1,000.00		\$ 1,000.00
CURB INLET DI-3 SERIES	4	EACH	\$ 1,500.00		\$ 6,000.00
GRATE INLET DI-5,7 SERIES	3	EACH	\$ 1,200.00		\$ 3,600.00
MANHOLE MH-2 SERIES	1	EACH	\$ 1,200.00		\$ 1,200.00
MANHOLE MH-	••	EACH	\$		\$
15 -IN. HDPE PIPE	420	LIN. FT.	\$ 25.00		\$ 10,500.00
18 -IN. HDPE PIPE		LIN. FT.	\$ 25.00		<u> </u>
24 -IN. HDPE PIPE	152	LIN. FT.	\$ 40.00	`	\$ 6,080.00
24 -IN. CONCRETE PIPE, CLASS III	62	LIN. FT.	\$ 50.00		\$ 3,100.00
30 -IN. CONCRETE PIPE, CLASS V	282	LIN. FT.	\$ 60.00		\$ 16,920.00
15 -IN. C.M. CULVERT	150	LIN. FT.	\$ 20.00		\$ 3,000.00
35 -IN. SPAN X 24" HEIGHT C.M. PIPE ARCH CULVERT	30	LIN. FT.	\$ 40.00		\$ 1,200.00
BOX CULVERT		LIMAD CLIMA			<u>e</u>
DOA CULVER!	••	LUMP SUM	\$		\$
EC-2 DITCH LINING	1,350	LIN. FT.	\$ 4.00		\$ 5,400.00
EC-3A DITCH LINING	400	LIN. FT.	\$ 5.00		\$ 2,000.00
RIPRAP - CLASS I		BONDED WITH	EROSION CONTR	OL MEASURES	4 - <del>1</del>
RIPRAP - CLASS II		BONDED WITH	EROSION CONTR	OL MEASURES	
SODDED SWALE	••	S.Y.	. \$		\$
45.00.000000000000000000000000000000000		E A OLL	<b>A</b> 000 00		A 000.00
15 -IN. HDPE END SECTION  18 -IN. HDPE END SECTION	1	EACH EACH	\$ 200.00 \$ 250.00		\$ 200.00 \$ 250.00
24 -IN. END SECTION ES-1	1	EACH	\$ 300.00	1	\$ 300.00
30 -IN. END SECTION ES-1	2	EACH	\$ 400.00		\$ 800.00
OU-IN. END GEOTIONES !	-	27.071			<b>V</b> 000.00
SIDEWALK	1,480	LIN. FT.	\$ 5.00		\$ 7,400.00
CURB & GUTTER CG-6	1,700	LIN. FT.	\$ 12.00		\$ 20,400.00
VDOT STD. CG-9D ENTRANCES	2	EACH	\$ 500.00		\$ 1,000.00
STD. PAVEMENT SECTION	2,500	S.Y.	\$ 12.00		\$ 30,000.00
PAVEMENT/DRIVEWAY REPLACEMENT	550	S.Y.	\$ 8.00		\$ 4,400.00
GRAVEL SHOULDER	••	S.Y.	\$		\$
SURFACE TREATMENT	••	S.Y.	\$		\$
-IN, BIT, CONC.: TYPE BIN, BIT, CONC.: TYPE S-	••	S.Y. S.Y.	\$ \$		\$
-IN. BASE MATERIAL	••	C.Y.			•
-IN. SUBBASE MATERIAL	••	C.Y.	\$		\$
8 -IN. WET TAP	1	EACH	\$ 250.00		\$ 250.00
12 -IN. PVC WATERLINE	1,080	LIN. FT.	\$ 22.00		\$ 23,760.00
8 -IN. PVC WATERLINE	490	LIN. FT.	\$ 18.00		\$ 8,820.00
AIR RELEASE VALVE	1	EACH	\$ 500.00		\$ 500.00
FIRE HYDRANT ASSEMBLY	2	EACH	\$ 1,000.00		\$ 2,000.00
BLOW OFF ASSEMBLY	1	EACH	\$ 500.00		\$ 500.00
8 -IN. GATE VALVE, W/ VAULT, FRAME & COVER	3	EACH	\$ 500.00		\$ 1,500.00
12 -IN. GATE VALVE, W/ VAULT, FRAME & COVER	3	EACH	\$ 600.00 \$ 250.00		\$ 1,800.00 \$ 750.00
SINGLE WATER METTER SETTER  DOUBLE WATER METTER SETTER	12	EACH EACH	\$ 350.00		\$ 4,200.00
8-IN. CHECK VALVE	12	EACH	\$ 500.00	<u></u>	\$ 4,200.00
	•			<u> </u>	
8 -IN. SDR-35 SANITARY SEWERLINE	1,695	LIN. FT.	\$ 18.00		\$ 30,510.00
8 -IN. DUCTILE IRON SANITARY SEWERLINE	100	LIN. FT.	\$ 25.00		\$ 2,500.00
4 -IN. RESIDENTIAL LATERAL	27	EACH	\$ 300.00		\$ 8,100.00
STANDARD MANHOLE W/ FRAME & COVER	14	EACH	\$ 1,200.00		\$ 16,800.00
S.S. RESIDENTIAL PUMP & FORCEMAIN	••	EACH	\$		\$
LANDSCAPING		LUMP SUM	-		<u> </u>
AMENITIES (INCLUDING BUT NOT LIMITED TO TRAILS, ETC)		LUMP SUM	\$ \$		\$ \$
(11012001110 DOT 1101 LIMITED TO HAILS, ETO)		LOWIN SUM	*		<b>3</b>
SWM FACILITY		LUMP SUM	\$ 5,000.00		\$ 5,000.00
CONVERSION OF SEDIMENT BASIN TO SWM FACILITY		LUMP SUM	\$ 1,000.00		\$ 1,000.00
SWM FENCING	410	LIN. FT.	\$ 8.00		\$ 3,280.00
DOUBLE GATE	2	EACH	\$ 500.00		\$ 1,000.00
AS-BUILT PLANS (STORM SEWER SYSTEMS)		LUMP SUM	\$ 1,000.00		\$ 1,000.00
AS-BUILT PLANS (STORMWATER MANAGEMENT)		LUMP SUM	\$ 1,000.00@		\$ 1,000.00
SUB-TOTAL .				**************************************	\$ 239,520.00
10% CONTINGENCY					\$ 23,952.00
			Long and		\$263,472.00

HEREBY CERTIFY THAT THE FOREGOING ESTIMATE REFLECTS THE CURRENT IMPROVEMENT COSTS OF THIS PROJECT.



REFLECTING TOMORROW www.balzer.cc PLANNERS • ARCHITECTS ENGINEERS • SURVEYORS

**1208 Corporate Circle** Roanoke, Virginia 24018 Phone: 540/772-9580 FAX: 540/772-8050

15871 City View Drive Midlothian, Virginia 23113 Phone: 804/794-0571 FAX: 804/794-2635

448 Peppers Ferry Road Christiansburg, Virginia 24073 Phone: 540/381-4290 FAX: 540/381-4291

1561 Commerce Road Verona, Virginia 24482 Phone: 540/248-3220 FAX: 540/248-3221

DRAWN BY:


DESIGNED BY:

CHECKED BY:

**REVISIONS:** 

21710

Clair (For



03-25-10 04-30-10 05-27-10 07-07-10

CPB

CPB

01-08-10

I AM CERTIFIED BY THE STATE OF VIRGINIA AS A "RESPONSIBLE LAND DISTURBER." I SHALL BE RESPONSIBLE FOR THE IMPLEMENTATION OF TH EROSION AND SEDIMENT CONTROL PLAN AS

CERTIFICATE DATE: TELEPHONE NUMBER

REGISTERED LAND DISTURBER

SHEET No.:

JOB No.: R0900098.00