GENERAL NOTES

PRE-CONSTRUCTION MEETING AND CONSTRUCTION COMMENCEMENT

- All construction methods and materials shall conform to the Construction Standards and Specifications of Roanoke County, the Western Virginia Water Authority, and the Virginia Department of Transportation.
- Stormwater Management Agreements with an attached 8 1/2" x 11" or 8 1/2" x 14" plat must be approved and recorded prior to the pre-construction meeting.
- Once all required items are submitted to the County of Roanoke, the developer must contact the Development Review Coordinator to indicate that a pre-construction meeting needs to be scheduled. The pre-construction meeting be scheduled with the owner/developer two (2) working days later.
- be Sindelined with the conference per two (,) withing gays are softened control of A. All and distallating projects that require approved of an expension and sediment control of an individual who will be responsible for land distallating activities and that this individual hold a Responsible Land Distaltative (LDL) certificate from the Department of Environmental Coally. The Responsible Land Distaltative can be anyone from the Project learn that a conflict of pix commonwealth of Wigning to be in charge of carrying out the land disturbing activity for the project
- It is the responsibility of the owner/developer to notify the certified Responsible Land Disturber and the Utility Contractor to attend the pre-construction meeting.
- The Development Review Coordinator will schedule the pre-construction meeting with the County Review Engineer, the County Inspector, and the Western Virginia Water Authority and the Town of Vinton Public Works Department if applicable.

- 9. The project engineer will inform the owner/developer verbally and in writing of the
- 10. The Erosion Control Permit or Combined Erosion Control & VSMP Permit is given to
- Notify the County of Roanoke prior to beginning installation of ESC measures. The County will inspect initial installations to ensure compliance with approved plan prior to start of grading. The developer SHALL contact the project inspector 24 hours before beginning any grading or construction on the property.
- County inspectors must inspect storm drain / stormwater management / BMP installations during the process of installation. Please contact the site inspector 24 hours in advance.
- 14. Contractors shall notify utilities of proposed construction at least two (2), but not more than ten (10) working days in advance. Area public utilities may be notified thru "Miss Utility": 1-800-552-7001 or VA 811,
- 15. The 100 year Floodway shall be staked prior to any construction.
- Grade stakes shall be set for all curb and gutter, culvert, sanitary sewer and storm sewer at all times of construction.
- The Department of Community Development shall be notified when a spring is encountered during construction.
- Construction debris shall be containerized in accordance with the Virginia Litter Control Act. No less than one litter receptacle shall be provided on site.
- 19. The contractor shall provide adequate means of cleaning mud from trucks and/or other equipment prior to entering public streets or rights of ways. It is the contractors responsibility to insure that the streets are in a clean, mud and dust free condition at all times.
- 21. Field construction shall honor proposed drainage divides as shown on plans.
- The developer or contractor shall supply the County and the Western Virginia Water Authority with correct As-Built plans before final acceptance.

VIRGINIA DEPARTMENT OF TRANSPORTATION:

- 24. Plan approval by Roanoke County does not guarantee issuance of any permits by the
- A permit must be obtained from the Virginia Department of Transportation, Salem Residency Office prior to construction in the highway right-of-way.
- The preliminary pavement designs should be based on a predicted sub-grade CBR value of 7.0 and with a Resiliency Factor (RF) of 2.0 as shown in Appendix I of the 2000 Virginia Department of Transportation Pavement Design Guide for Subdivision. 2000 Virginia Department of Transportation Pawement Design Guide for Subdivision and Secondary Roads. The sub-grade oil is to be tested by an independent prior laboratory and the results submitted to the Virginia Department of Transportation prior to base construction. Should the sub-grade CBR Value and ord the RF value be less than the predicted values, additional base material will be required in accordance with Departmental specifications. Refer to the same manural as the number and locations
- Departmental aportionations. Refer to the same manual as the number and locations of the required oad samples to be tested. All powermed designs shall be submitted to the Department for review and approved. The sub-gased shall be approved by the partment for review and approved. The sub-gased shall be approved by the partment for review and approved by the registral bepartment of transportation for depth, Inequitate, and compaction before the surface is applied. Standard guardest with safety and sections may be required on fills or in areas where the country Engineer and Virginia Department of Transportation for address the country Engineer and Virginia Department of Transportation shall be consided to about the country Engineer and Virginia Department of Transportation shall be considered to about the country Engineer and Virginia Department of Transportation shall be considered to accordance with the 2001 shall be considered as the considered to the part of shall be remisted as the intersection to the same of the country of
- Standard street and traffic control signs shall be erected at each intersection by the developer prior to final street acceptance.

See Sheet C4 for Stormwater Site Statistics Table.
See Sheet NA for New BMP Information Table.

The notes on this sheet shall not be modified



COUNTY OF ROANOKE, VA

VILLAGE GREEN APARTMENTS ROANOKE VALLEY INVESTMENTS, LLC P.O. BOX 20886 ROANOKE, VA 24018 ROANOKE VALLEY INVESTMENTS, LLC DEVELOPER (name, address, telephone) P.O. BOX 20886 ROANOKE, VA 24018 ROANOKE, VA 24018 ATTN: BEN CREW 540-772-9580 FAX 540-772-8050 TAX MAP NO(S) PORTION OF 027.17-04-13.03-0000

WATER NOTES


All water facilities shall be constructed according to the Western Virginia Regional Design and Construction Standards (Latest Edition).

A minimum cover of three (3) feet is required over proposed lines

Contractor shall be responsible for locating and uncovering valve vaults after paying and adjustment to final grade if necessary.

Water main shall be minimum Class 350 Ductile Iron in accord
AWWA C151 or DR-14 PVC in accordance with AWWA C-900

Ductile Iron Pipe in accordance with the Western Virginia Regional Design and Construction Standards shall be required for all pipe with a working pressure equal to or greater than 100 p.s.i,



LEGEND

	ELGEND
Property Line	
Right-of-way	
Centerline	
Minimum Building Line	
Existing Storm Sewer	48"RCP 48"RCP
Existing Sanitary Sewer	
Existing Water Main	
Existing Contour	
Proposed Contour	<u></u>
Proposed Drainage Divide	
Proposed Limits of Clearing	
Proposed Storm Sewer	
Proposed Sanitary Sewer	8" SS
Proposed Water Main	

T.B.R.

To Be Removed

SEWER NOTES

All sanitary sewer facilities shall be installed according to the Western Virginia Regional Design and Construction Standards. (Latest Edition).


A minimum cover of three (3) feet is required over proposed lines.

Contractor shall be responsible for locating and uncovering all manholes after paving. Manhole tops shall be adjusted to grade if necessary.

All trenches in existing or future rights-of-way shall be compacted according to Virginia Department of Transportation standards. Lines shall be staked prior to construction.

PRIVATE UTILITIES

Indeerground utilities installed on private property or in private little generated and building related some dinaries all be designed and installed per the current edition of the Virginia Uniform Statewide Building Code. Design and installation requirements issued by the Western Virginia Water Mortority that meet occure the USBC requirements are acceptable for private utilities. All private utilities are to be permitted through and impacted by the Roander Courtly inspections Office



SURVEY INFORMATION

Horizontal and vertical control By: BALZER		erformed in year: S, INC. (B & A INC.)	2016
All vertical elevations must be All horizontal elevations must			
Horizontal Datum: 19	183	Vertical Datum:	1988
Source of topographic mapping	ng is dated	MAY 2016	
Boundary was performed by_	B & A INC.	dated:	JULY 2016
Benchmark Information:	EX. STORM S	SEWER MANHOLE	
	TOP=1077.14		

The professional seal and signature certifies the boundary survey and topographic mapping to be accurate and correct.

"NOTE: THIS COST ESTIMATE TABLE IS PROVIDED FOR BONDING PURPOSES ONLY. VERIFICATION OF ALL QUANTITIES AND PRICES FOR BIDDING PURPOSES SHALL BE THE RESPONSIBILITY OF THE BIDDER."

QUANTITY & COST ESTIMATE QUANTITY UNIT UNIT PRICE ACRES 1,000.00 C.Y. VDOT STD DI-3C EACH 1,500.00 1,500.00 7,500,00 10° TYPE 9 UNDE DID 15" TYPE S HDPE PIPE LIN. FT. 18" TYPE S HDPE PIPE LIN. FT. 35.00 595.00 ONCRETE HEADWA EACH 400.00 PAVED DITCH LIN. FT. IPRAP - CLASS S.F. ODDED SWALE S.Y. -IN. CONCRETE ENDWALL FW-PAVEMENT /INCLUDING SUB-BASE CURB & GUTTER CG-6 LIN, FT. URFACE TREATMENT -IN. BIT. CONC.: TYPE S S.Y. C.Y. OMMERCIAL WATER FIRE & DOMESTIC VAULTS \$ 8,500.00 EACH BLOW OFFS WIVAULT, FRAME & COVE -IN. GATE VALVE, WIVAULT, FRAME & COVER EACH 8" PVC SANITARY SEWER LATERAL 128 UN. FT. \$ 35.00 \$4.480.00 ANDROADING (SEE SHEET C. 15) AS-BUILT PLANS - SWM & STORM SEWER LUMP SUM \$ 2,000.00 \$ 2,000.00 ESTIMATED TOTAL \$ 188 780 BY SEALING THE PLANS, THE DESIGN PROFESSIONAL HEREBY CERTIFIES THAT THE FOREGOING ESTIMATE REFLECTS THE CURRENT IMPROVEMENT COSTS OF THIS PROJECT.

PLANNERS • ARCHITECTS ENGINEERS • SURVEYORS

1208 Corporate Circle Roanoke, Virginia 24018 Phone: 540/772-9580 FAX: 540/772-8050

Christopher P. Burns Lic. No.047338 5/15/19

Revision

an

DESIGNED BY: BTC CHECKED BY: CPB 10/25/2016 12/2/2016 REVISIONS: 12/29/2016

5/15/2019 P.R. #1



Virginia

Roanoke,

₹

6961 ₽

N N N GREE LANE GRI Ш CAREFR R <u>ত</u> ₹

JOB No.: 04160011.00