

## GENERAL NOTES

### PRE-CONSTRUCTION MEETING AND CONSTRUCTION COMMENCEMENT:

- All construction methods and materials shall conform to the Construction Standards and Specifications of Roanoke County, the Western Virginia Water Authority, and the Virginia Department of Transportation.
- Stormwater Management Agreements with an attached 8 1/2" x 11" or 8 1/2" x 14" plat must be approved and recorded prior to the pre-construction meeting.
- Once all required items are submitted to the County of Roanoke, the developer must contact the Development Review Coordinator to indicate that a pre-construction meeting needs to be scheduled. The pre-construction meeting will be scheduled with the owner/developer two (2) working days later.
- All land disturbing projects that require approval of an erosion and sediment control plan, grading or clearing permit shall require that the applicant provide the name of an individual who will be responsible for land disturbing activities and that this individual hold a Responsible Land Disturber (RLD) Certificate from the Department of Environmental Quality. The Responsible Land Disturber can be anyone from the Project team that is certified by the Commonwealth of Virginia to be in charge of carrying out the land disturbing activity for the project.
- It is the responsibility of the owner/developer to notify the certified Responsible Land Disturber and the Utility Contractor to attend the pre-construction meeting.
- The Development Review Coordinator will schedule the pre-construction meeting with the County Review Engineer, the County Inspector, and the Western Virginia Water Authority and the Town of Vinton Public Works Department if applicable.
- An approved set of plans, Storm Water Pollution Prevention Plan (SWPPP), VSMP coverage letter, and all permits must be available at the construction site at all times.
- The developer and/or contractor shall supply all utility companies with copies of approved plans, advising them that all grading and installation shall conform to approved plans.
- The project engineer will inform the owner/developer verbally and in writing of the County's obligation to perform inspections on site. Everyone in the meeting will be required to sign a pre-construction checklist indicating their knowledge of Roanoke County's obligation to perform inspections on site.
- The Erosion Control Permit or Combined Erosion Control & VSMP Permit is given to the developer at this pre-construction meeting.
- Notify the County of Roanoke prior to beginning installation of ESC measures. The County will inspect initial installations to ensure compliance with approved plan prior to start of grading. The developer SHALL contact the project inspector 24 hours before beginning any grading or construction on the property.
- County inspectors must inspect storm drain / stormwater management / BMP installations during the process of installation. Please contact the site inspector 24 hours in advance.
- All work shall be subject to inspection by Roanoke County, the Western Virginia Water Authority and the Virginia Department of Transportation inspectors.
- Contractors shall notify utilities of proposed construction at least two (2), but not more than ten (10) working days in advance. Area public utilities may be notified thru "Miss Utility": 1-800-552-7001 or VA 811.
- The 100 year Floodway shall be staked prior to any construction.
- Grade stakes shall be set for all curb and gutter, culvert, sanitary sewer and storm sewer at all times of construction.
- The Department of Community Development shall be notified when a spring is encountered during construction.
- Construction debris shall be containerized in accordance with the Virginia Litter Control Act. No less than one litter receptacle shall be provided on site.
- The contractor shall provide adequate means of cleaning mud from trucks and/or other equipment prior to entering public streets or rights of ways. It is the contractors responsibility to insure that the streets are in a clean, mud and dust free condition at all times.
- Plan approval in no way relieves the developer or contractors of the responsibilities contained within the erosion and sediment control or stormwater management policies.
- Field construction shall honor proposed drainage divides as shown on plans.
- Field corrections shall be approved by the Roanoke County Engineering Division and/or the Western Virginia Water Authority and the Professional of Record, prior to such construction.
- The developer or contractor shall supply the County and the Western Virginia Water Authority with correct As-Built plans before final acceptance.


### VIRGINIA DEPARTMENT OF TRANSPORTATION:

- Plan approval by Roanoke County does not guarantee issuance of any permits by the Virginia Department of Transportation.
- A permit must be obtained from the Virginia Department of Transportation, Salem Residency Office prior to construction in the highway right-of-way.
- The preliminary pavement designs should be based on a predicted sub-grade CBR value of 7.0 and with a Resiliency Factor (RF) of 2.0 as shown in Appendix I of the 2000 Virginia Department of Transportation Pavement Design Guide for Subdivision and Secondary Roads. The sub-grade soil is to be tested by an independent laboratory and the results submitted to the Virginia Department of Transportation prior to base construction. Should the sub-grade CBR value and/or the RF value be less than the predicted values, additional base material will be required in accordance with Departmental specifications. Refer to the same manual as the number and locations of the required soil samples to be tested. All pavement designs shall be submitted to the Department for review and approval. The sub-grade shall be approved by the Virginia Department of Transportation prior to placement of the base. Base shall be approved by the Virginia Department of Transportation for depth, template, and compaction before the surface is applied.
- Standard guardrail with safety end sections may be required on fills or in areas where hazards exist as deemed necessary. After completion of rough grading operations, the County Engineer and Virginia Department of Transportation shall be contacted to schedule a field review. Where guard rail is warranted, the standard shoulder width shall be provided and the guard rail shall be installed in accordance with the 2001 VDOT Road and Bridge Standards as part of this development.
- Standard street and traffic control signs shall be erected at each intersection by the developer prior to final street acceptance.
- All traffic devices shall be in accordance with current edition of the "Manual on Uniform Traffic Control Devices" (MUTCD).
- All unsuitable material shall be removed from the construction limits of the roadway before placing embankment.

See Sheet C-9 for Stormwater Site Statistics Table.  
See Sheet C-9 for New BMP Information Table.

The Project Engineer shall provide electronic copies of the approved plans to the Development Review Coordinator within 5 working days of the pre-construction meeting.

The notes on this sheet shall not be modified.



# COUNTY OF ROANOKE, VA

NAME OF DEVELOPMENT	THE VILLAGE AT TINKER CREEK - PHASE IIIA	I, _____, OWNER/DEVELOPER, AM AWARE OF THE SITE DESIGN REQUIREMENTS IMPOSED BY THIS SITE DEVELOPMENT PLAN AND OTHER APPLICABLE ROANOKE COUNTY CODES. I HEREBY CERTIFY THAT I AGREE TO COMPLY WITH THESE REQUIREMENTS AND THE THIRTY (30) POINTS SHOWN ON THIS COVER SHEET UNLESS MODIFIED IN ACCORDANCE WITH LOCAL LAW.
MAGISTERIAL DISTRICT(S)	HOLLINS	
OWNER (name, address, telephone)	TINKER CREEK DEVELOPERS, LLC 819 WALHALLA COURT, ROANOKE, VA 24019 PHONE: (540) 444-2111 ATTN. MR. NORM MASON	
DEVELOPER (name, address, telephone)	TINKER CREEK DEVELOPERS, LLC 819 WALHALLA COURT, ROANOKE, VA 24019 PHONE: (540) 444-2111 ATTN. MR. NORM MASON	
ENGINEER, ARCHITECT OR SURVEYOR (name, address, telephone)	MATTERN AND CRAIG, INC. 701 FIRST STREET SW, ROANOKE, VA 24016 PHONE: (540) 345-9342 ATTN. MR. TOM AUSTIN, P.E.	
TAX MAP NO(S)	027.20-01-39.02-0000 (PROJECT SITE) - TO BE SUBDIVIDED	

## WATER NOTES

All water facilities shall be constructed according to the Western Virginia Regional Design and Construction Standards (Latest Edition).

A minimum cover of three (3) feet is required over proposed lines.

Contractor shall be responsible for locating and uncovering valve vaults after paving and adjustment to final grade if necessary.

All existing utilities may not be shown in their exact location. The contractor shall comply with the (State Water Works Regulations, Section 12VAC5-590-1150, where lines cross.


All trenches in existing or future highway right-of-ways shall be compacted according to Virginia Department of Transportation standards.

Lines shall be staked prior to construction.

Water main shall be minimum Class 350 Ductile Iron in accordance to AWWA C151 or DR-14 PVC in accordance with AWWA C-900.

Ductile Iron Pipe in accordance with the Western Virginia Regional Design and Construction Standards shall be required for all pipe with a working pressure equal to or greater than 100 p.s.i.

Western Virginia Water Authority  
Availability letter number: 15-156



## LEGEND

Property Line	---
Right-of-way	--- P/W ---
Centerline	--- CL ---
Minimum Building Line	--- MBL ---
Existing Storm Sewer	--- SD ---
Existing Sanitary Sewer	--- SS ---
Existing Water Main	--- W ---
Existing Contour	--- 1045 ---
Proposed Contour	--- 1045 ---
Proposed Drainage Divide	--- 24" S.D. ---
Proposed Limits of Clearing	--- 8" M.H. ---
Proposed Storm Sewer	--- HYDRANT ---
Proposed Sanitary Sewer	--- VALVE ---
Proposed Water Main	--- BLOWOFF ---

## SEWER NOTES

All sanitary sewer facilities shall be installed according to the Western Virginia Regional Design and Construction Standards. (Latest Edition).

A minimum cover of three (3) feet is required over proposed lines.

Contractor shall be responsible for locating and uncovering all manholes after paving. Manhole tops shall be adjusted to grade if necessary.

All existing utilities may not be shown in their exact location. The contractor shall comply with (State Water Works Regulations, Section 12VAC5-590-1150, where lines cross.)

All trenches in existing or future rights-of-way shall be compacted according to Virginia Department of Transportation standards.

Lines shall be staked prior to construction.

## PRIVATE UTILITIES

Underground utilities installed on private property or in private utility easements and building related storm drains shall be designed and installed per the current edition of the Virginia Uniform Statewide Building Code. Design and installation requirements issued by the Western Virginia Water Authority that meet or exceed the USBC requirements are acceptable for private utilities. All private utilities are to be permitted through and inspected by the Roanoke County Inspections Office. Vaults, valves and other devices installed by or under the control of the Western Virginia Water Authority may not substituted for the code required devices.

## Sheet Index

- |       |  |
|-------|--|
| C-1   | COVER SHEET  |
| C-2   | OVERALL LAYOUT & OPEN SPACE PLAN                             |
| C-3   | PHASING PLAN   |
| C-4   | LAYOUT, WATER, & SANITARY SEWER PLAN                         |
| C-5   | PROFILES - ROADS, WATER, & SANITARY SEWER                    |
| C-6   | UTILITY DETAILS - WWA WATER                                  |
| C-7   | UTILITY DETAILS - WWA SEWER                                  |
| C-8   | UTILITY DETAILS - WWA WATER & SEWER                          |
| C-9   | GRADING AND STORM DRAINAGE PLAN                              |
| C-10  | PROFILES - STORM DRAINAGE                                    |
| C-10A | PROFILES - STORM DRAINAGE                                    |
| C-11  | DETAILS & SECTIONS   |
| C-12  | NOT USED   |
| C-12A | NOT USED   |
| EC-1  | EROSION & SEDIMENT CONTROL PLAN - STAGE I                    |
| EC-2  | EROSION & SEDIMENT CONTROL PLAN - STAGE II                   |
| EC-3  | EROSION & SEDIMENT CONTROL NARRATIVE                         |
| EC-4  | EROSION & SEDIMENT CONTROL STATEMENT OF COMPLIANCE           |
| EC-5  | EROSION & SEDIMENT CONTROL DETAILS                           |
| EC-6  | EROSION & SEDIMENT CONTROL DETAILS                           |
| EC-7  | EROSION & SEDIMENT CONTROL DETAILS                           |
| LG-1  | LOT GRADING PLAN   |
| D-1   | PRE-DEVELOPMENT DRAINAGE DIVIDES (PHASE IIIA)                |
| D-2   | POST-DEVELOPMENT DRAINAGE DIVIDES (PHASE IIIA) & LOT GRADING |
| D-3   | POST-DEVELOPMENT DRAINAGE DIVIDES (FUTURE PHASE)             |

## SURVEY INFORMATION

Horizontal and vertical control surveys were performed in year: 2014  
By: MATTERN AND CRAIG, INC. 701 FIRST STREET SW, ROANOKE, VA 24016

All vertical elevations must be referenced to the National Geodetic Vertical Datum of 1929 or 1988. All horizontal elevations must be referenced to the North American Datum of 1927 or 1983.

Horizontal Datum: PER PLAT INST. Vertical Datum: NGVD88  
#201000283 \*  
Source of topographic mapping is dated AUG. 2014

Boundary was performed by M&C, INC. dated: AUG. 2014

Benchmark Information: P/PIPK NAIL IN STUMP, EL.=1079.88.  
SEE SHEET C-4 FOR LOCATION AND BENCHMARK TABLE.

The professional seal and signature certifies the boundary survey and topographic mapping to be accurate and correct.

\* Based on Virginia State Plane Coordinate System

## QUANTITY & COST ESTIMATE (FOR BONDING PURPOSE)

ITEM	QUANTITY	UNIT	UNIT PRICE	COST	BONDABLE
CLEARING & GRUBBING	0.25	AC			
EXCAVATION	7,500	CY			
EMBANKMENT	7,500	CY			
TOPSOIL STRIPPING	750	CY			
CURB INLET D&G, L=6'	0.5	EA	2,400	\$1,200	\$1,200
CURB INLET D&G	0.5	EA	2,200	\$1,100	\$1,100
MANHOLE (MH-1) 4' DIA / 4'-6" Deep	3	EA	2,800	\$8,400	\$8,400
MANHOLE (MH-1) 5' DIA / 4'-6" Deep	0.5	EA	3,200	\$1,600	\$1,600
18-IN. CONCRETE PIPE, CLASS III	34	LF	48.00	\$1,632	\$1,632
24-IN. CONCRETE PIPE, CLASS III	411	LF	62.00	\$25,482	\$25,482
XX-IN. CM CULVERT		LF			
XX-IN. CM CULVERT		LF			
BOX CULVERT		LS			
PAVED SWALE		LF			
RIPRAP - CLASS		SF			
PERMANENT GRASS SWALE		LF			
24-IN. CONCRETE ENDWALL EW-1	0.5	EA	2,800	\$1,400	\$1,400
24-IN. END SECTION ES-1	1	EA	2,800	\$2,800	\$2,800
18-IN. END SECTION ES-1	0.5	EA	2,200	\$1,100	\$1,100
HEADER CURB & GUTTER CG-2		LF			
CURB & GUTTER CG-4 (PUBLIC STREET)	360	LF	20.00	\$7,200	\$7,200
VALLEY GUTTER (PRIVATE STREET)	475	EA	20.00	\$9,500	\$9,500
GRAVEL BASE		SY			
GRAVEL SHOULDER		SY			
SURFACE TREATMENT		SY			
3-IN. BIT. CONC. BASE COURSE, TYPE BM-25	760	SY	10.00	\$7,600	\$7,600
2-IN. BIT. CONC. SURFACE COURSE, TYPE SM-9.5A	590	SY	6.75	\$3,963	\$3,963
1.5-IN. BIT. CONC. SURFACE COURSE, TYPE SM-9.5A	760	SY	5.00	\$3,800	\$3,800
6-IN. AGGREGATE BASE MATERIAL	460	TN	18.00	\$8,280	\$8,280
XX-IN. SUBBASE MATERIAL		CY			
TRAFFIC BARRICADE		EA			
8" WATER LINE	400	LF	40.00	\$16,000	\$16,000
6" WATER LINE		LF			
DOMESTIC SERVICES	12	EA	1,500	\$18,000	\$18,000
4-IN. WATER LATERALS		EA			
BLOW OFFS W/ 9-IN. VAULT, FRAME & COVER	1	EA	1,400	\$1,400	\$1,400
8-IN. GATE VALVES W/ VAULT, FRAME & COVER	2	EA	1,200	\$2,400	\$2,400
6-IN. GATE VALVES W/ VAULT, FRAME & COVER	-	EA			
FITTINGS (TEES, BENDS, ETC.)	5	EA	600	\$3,000	\$3,000
AIR RELEASE VALVE	1	EA	1,200	\$1,200	\$1,200
8" SANITARY SEWER	62	LF	50	\$3,100	\$3,100
8" SANITARY SEWER	546	LF	50	\$27,300	\$27,300
4-INCH SEWER LATERALS WITH CLEAN-OUT	16	EA	1,500	\$24,000	\$24,000
STANDARD 4-FOOT DIA. MANHOLE W/ FRAME & COVER	4	EA	3,000	\$12,000	\$12,000
STANDARD 4-FOOT DIA. MANHOLE W/ FRAME & COVER		EA			
SAMPLING MANHOLE / PORT	-	EA			
LANDSCAPING		LS			
AMENITIES (INCLUDING BUT NOT LIMITED TO TRAILS, ETC.,)		LS			
STORMWATER MANAGEMENT (WATER QUALITY)	1	LS	92,500	\$92,500	\$92,500
AS-BUILT PLANS (STORM SEWER SYSTEMS)	1	LS	1,000	\$1,000	\$1,000
AS-BUILT PLANS (STORMWATER MANAGEMENT)	1	LS	600	\$600	\$600
SUBTOTAL				\$294,577	
10% CONTINGENCY				\$29,458	
ESTIMATED TOTAL				\$324,035	
BY SEALING THE PLANS, THE DESIGN PROFESSIONAL HEREBY CERTIFIES THAT THE FOREGOING ESTIMATE REFLECTS THE CURRENT IMPROVEMENT COSTS OF THIS PROJECT.					



REVISIONS	DATE
1. 1ST REVIEW COMMENTS	7/17/15
2. APPROVED SET	9/4/15
3. PLAN REVISION NO. 1	7/21/17
4. PLAN REVISION NO. 2	3/12/20

SB-1501065  
PLAN  
REVISION  
NO. 2



PLAN APPROVED  
Dennis J. Smith  
REVIEW COORDINATOR: 4/14/2020

THE VILLAGE AT TINKER CREEK - PHASE IIIA  
VILLAGE AT TINKER CREEK, LLC

COVER SHEET

ROANOKE COUNTY, VIRGINIA

SHEET  
C-1

**Mattern & Craig, Inc.**

CONSULTING ENGINEERS • SURVEYORS

701 FIRST STREET, S.W.

ROANOKE, VIRGINIA 24016

(540) 345-9342

FAX (540) 345-7691